WaterChef Brand, Model C7000 Countertop Filtration System

Water Safety Corporation 3760 Barron Way, Reno, NV, 89511 775-359-9500 WaterChef.com

WATERCHEF COUNTERTOP FILTRATION SYSTEM (C7000)

Installation	Housing Construction
EPA Establishment Number	Maximum Working Pressure
Rated Capacity 1,000 gallons (3,785 L)	Minimum Working Pressure
Replacement Filter Cartridge	Maximum Operating Temperature (for cold water use only) 100° F/38° C
Replacement Battery (included with CR70)2032 CR, 3V lithium	Minimum Operating Temperature
Filter Life Indicator Electronic LED	Particle Retention Size Sub-Micron (0.5 micron)
Rated Service Flow 0.65 gal/min @ 60 psi	U.S. Patent Number: D408,494

NSF/ANSI STANDARD 42 (Aesthetic Effects)

NSF Certified Performance Claims:

Chlorine Reduction
Chloramine Reduction
Nominal Particulate Reduction, Class 1
Taste and Odor Reduction
Cyst Reduction
Lead Reduction

MTBE Reduction

VOC Reduction

This System has been tested according to NSF/ANSI Standard 42 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42.

SUBSTANCE	INFLUENT CHALLENGE CONCENTRATION	REDUCTION REQUIREMENT	ACTUAL % REDUCTION
chlorine	2.0 mg/L ± 10%	≥50%	93.1%
chloramine	3.0 mg/L ± 10%	0.5 mg/L	93.1%
particulate*	at least 10,000 particles/mL	≥85%	>99%

^{*}Class I particles 0.5 to <1 µm

http://www.waterchef.com/images/documents/WaterChef-Performance-Data-Sheet-C7000.pdf

NSF/ANSI STANDARD 53 (Health Effects)

This system has been tested according to NSF/ANSI Standard 53 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 53.

SUBSTANCE	INFLUENT CHALLENGE CONCENTRATION (mg/L)	MAX. PERMISSIBLE PRODUCT WATER CONCENTRATION (mg/L)	CHEMICAL REDUCTION PERCENT
alachlor	0.050	0.001	>98%
atrazine	0.100	0.003	>97%
benzene	0.081	0.001	>99%
carbofuran	0.190	0.001	>99%
carbon tetrachloride	0.078	0.0018	98%
chlorobenzene	0.077	0.001	>99%
chloropicrin	0.015	0.0002	99%
2,4-D	0.110	0.0017	98%
dibromochloropropane (DBC	P) 0.052	0.00002	>99%
o-dichlorobenzene	0.080	0.001	>99%
p-dichlorobenzene	0.040	0.001	>98%
1,2-dichloroethane	0.088	0.0048	>95%
1,1-dichloroethylene	0.083	0.001	>99%
cis-1,2-dichloroethylene	0.170	0.0005	>99%
trans-1,2-dichloroethylene	0.086	0.001	>99%
1,2-dichloropropane	0.080	0.001	>99%
cis-1,3-dichloropropylene	0.079	0.001	>99%
dinoseb	0.170	0.0002	99%
endrin	0.053	0.00059	99%
ethylbenzene	0.088	0.001	>99%
ethylene dibromide (EDB)	0.044	0.00002	>99%
haloacetonitriles (HAN):			
bromochloroacetonitrile	0.022	0.0005	98%
dibromoacetonitrile	0.024	0.0006	98%
dichloroacetonitrile	0.0096	0.0002	98%
trichloroacetonitrile	0.015	0.0003	98%
haloketones (HK):			
1,1,-dichloro-2-propanone	0.0072	0.0001	99%
1,1,1-trichloro-2-propanon	e 0.0082	0.0003	96%
heptachlor (H-34, Heptox)	0.08	0.0001	>99%

[continued]

	INFLUENT CHALLENGE CONCENTRATION (mg/L)	MAX. PERMISSIBLE PRODUCT WATER CONCENTRATION (mg/L)	CHEMICAL REDUCTION PERCENT
heptachlor epoxide	0.0107	0.0002	98%
hexachlorobutadiene	0.044	0.001	>98%
hexachlorocyclopentadiene	0.060	0.000002	>99%
lindane	0.055	0.00001	>99%
methoxychlor	0.050	0.0001	>99%
pentachlorophenol	0.096	0.001	>99%
simazine	0.120	0.004	>97%
styrene	0.150	0.0005	>99%
1,1,2,2-tetrachloroethane	0.081	0.001	>99%
tetrachloroethylene	0.081	0.001	>99%
toluene	0.078	0.001	>99%
2,4,5-TP (silvex)	0.270	0.0016	99%
tribromoacetic acid	0.042	0.001	>98%
1,2,4-trichlorobenzene	0.160	0.0005	>99%
1,1,1-trichloroethane	0.084	0.0046	>95%
1,1,2-trichloroethane	0.150	0.0005	>99%
trichloroethylene	0.180	0.001	>99%
trihalomethanes (includes):			
chloroform (surrogate chemi	ical) 0.300	0.015	95%
bromoform			
bromodichloromethane			
chlorodibromomethane			
xylenes (total)	0.070	0.001	>99%

SUBSTANCE	INFLUENT CHALLENGE	REDUCTION	ACTUAL %
	CONCENTRATION	REQUIREMENT	REDUCTION
cyst (cryptosporidium, giardia)	min. 50,000/L	99.95%	>99.99%

SUBSTANCE	INFLUENT CHALLENGE CONCENTRATION (mg/L)	MAX. PERMISSIBLE PRODUCT WATER CONCENTRATION (mg/L)	CHEMICAL REDUCTION PERCENT
lead (pH 6.5)	0.15 ± 10%	0.010	>99%
lead (pH 8.5)	0.15 ± 10%	0.010	>99%
MTBE (methyl tert-butyl ether)	0.015 ± 10%	0.005	>94.3%

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the System. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.
- 2. For use on cold, potable water supplies only.
- 3. For this System to continue to perform as tested and represented, use only genuine, NSF certified WaterChef® CR70 filter cartridges. Replace the filter cartridge when the first of the following occurs:
 - Annually
 - · The flow rate diminishes
 - · When the rated capacity of the filter cartridge has been reached
 - . When you notice a taste or odor recurrence
- Installation of this product must comply with all state and local laws and regulations.
 Refer to your local agencies for details.
- The contaminants or other substances removed or reduced by this Drinking Water System are not necessarily in all users' water.
- 6. Individuals requiring specific microbiological purity should consult their physician.
- For limited warranty and installation and operating instructions, please refer to the Installation, Use & Care Guide.

- 8. The approximate cost for a filter cartridge is \$55.00 or less.
- For more information regarding the purchase of genuine, NSF certified WaterChefer filter cartridges and replacement parts, contact:

WaterChef Customer Care 3760 Barron Way Reno, NV 89511 tel: 1.800.879.8909 email: customercare@waterchef.com

ABBREVIATIONS:

ug/L: Micrograms per liter Mg/L: Milligrams per liter NTU: Nephelametric Turbidity Unit

MCL: Maximum Contaminant Level VOC: Volatile Organic Compound

US-EPA: United States Environmental Protection Agency

See Installation, Use & Care Guide for general operation and maintenance requirements and the manufacturer's warranty. http://www.waterchef.com/images/documents/WaterChef-Installation-Manual-C7000-Countertop.pdf