

**California Regional Water Quality Control Board
San Diego Region**

**ADDITIONAL
DRAFT UPDATES & ERRATA**

to the
AUGUST 12, 2009 PUBLIC RELEASE DRAFT

of the

**Waste Discharge Requirements for Discharges of Runoff from
the Municipal Separate Storm Sewer Systems (MS4s)
Draining the Watershed of the County of Orange, the
Incorporated Cities of Orange County, and the Orange County
Flood Control District within the San Diego Region**

**Tentative Order No. R9-2009-0002
NPDES NO. CAS0108740**

**ADDITIONAL ERRATA & UPDATES AS OF
16 December 2009**

This document represents additional tentative updates and errata to the August 12, 2009 release of Tentative Order No. R9-2009-0002. These updates and errata are in addition to those provided to the Regional Board at the November 18, 2009 meeting as Supporting Document No. 2. The errata represent minor clarifications and reference mistakes identified by Staff on the August 12, 2009 public release of draft Tentative Order No. R9-2009-0002. The updates include changes made at the Board's direction from the November 18, 2009 meeting.

Permit Errata

Pg. 38, Section F.1.d.(7) references "watershed equivalent BMP(s) consistent with Section F.1.c.(8)" should reference Section F.1.d.(11).

Permit Changes

Page 2. C. Discharge Characteristics. Additional Findings C. 3 and C.4:

3. This order is intended to regulate the discharge of pollutants from MS4s from anthropogenic (generated from human activities) sources and/or activities within the jurisdiction and control of the Copermittees and is not intended to address background or naturally occurring pollutants or flows.
4. The Copermittees may lack legal jurisdiction over certain discharges into their systems from some state and federal facilities, utilities, and special districts, Native American tribal lands, waste water management agencies and other point and non-point source discharges otherwise permitted by the Regional Board. The Regional Board recognizes that the Copermittees should not be held responsible for such facilities and/or discharges. Similarly, certain activities that generate pollutants may be beyond the ability of the Copermittees to eliminate. Examples of these include operation of internal combustion engines, atmospheric deposition, brake pad wear, tire wear and leaching of naturally occurring minerals from local geography.

Page 17, Finding E.12:

12. This Order requires each Copermittee to effectively prohibit all types of unauthorized discharges of non-storm water into its MS4. However, historically pollutants have been identified as present in dry weather non-storm water discharges from the MS4s through 303(d) listings, monitoring conducted by the Copermittees under Order No. R9-2002-0001, and there are others expected to be present in dry weather non-storm water discharges because of the nature of these discharges. This Order includes action levels for pollutants in non-storm water, dry weather, discharges from the MS4 designed to ensure that the requirement to effectively prohibit all types of unauthorized discharges of non-storm water in the MS4 is being complied with. Action levels in the Order are based upon numeric or narrative water quality objectives and criteria as defined in the Basin Plan, and the Water Quality Control Plan for Ocean Waters of California (Ocean Plan, NALs are not numeric effluent limitations.

Deleted:), and the State Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (State Implementation Policy or SIP)

Deleted: An

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

Exceedance of an action level requires specified responsive action by the Copermitees. This Order describes what actions the Copermitees must take when an exceedance of an action level is observed. Exceedances of non-storm water action levels do not alone constitute a violation of this Order; however they could indicate that more must be done to comply with the requirement to effectively prohibit all types of unauthorized non-storm water discharges into the MS4 or other prohibitions established in this Order. Failure to undertake required source investigation and elimination action following an exceedance of a non-storm water action level (NAL or action level) is a violation of this Order. However, establishing NALs at levels appropriate to protect water quality standards is expected to lead to the identification of significant sources of pollutants in dry weather non-storm water discharges.

Deleted: e

Deleted: but

Deleted: non-compliance

Deleted: The Regional Board recognizes that use of action levels will not necessarily result in detection of all unauthorized sources of non-storm water discharges because there may be some discharges in which pollutants do not exceed established action levels

Pg. 22 – Section C:

C. NON-STORM WATER DRY WEATHER ACTION LEVELS

1. Copermitees shall engage the Southern California Coastal Water Research Project (SCCWRP) to develop non-storm water dry weather action levels (NALs). The purpose of the NALs shall be to establish numeric action levels for pollutants in non-storm water, dry weather, discharges to ensure that the Copermitees effectively prohibit unauthorized discharges of non-storm water into their MS4s and to protect water quality. Copermitees shall also engage SCCWRP to develop an NAL implementation plan, consistent with this section, that specifies the actions the Copermitees will take in response to NAL exceedances. The implementation plan shall take into account the magnitude, frequency, and number of constituents exceeding the NALs. Copermitees shall submit the proposed NALs and implementation plan to the Executive Officer within 18 months of the Order effective date¹. Once approved by the Executive Officer, the NALs shall become effective immediately. Should the Copermitees fail to submit the NALs and implementation plan within 18 months, the action levels provided in Section C.6 shall become effective and Copermitees shall respond to NAL exceedances as provided in Section C.2.
2. In response to an exceedance of a NAL, each Copermitee must investigate and identify the source of the exceedance in a timely manner. Following the source investigation and identification, the Copermitees must submit an action report dependant on the source of the pollutant exceedance as follows:
 - a. If the Copermitee identifies the source of the exceedance as natural (non-anthropogenic) in origin; then the Copermitee shall report their findings and documentation of their source investigation to the Regional Board within thirty days of the source identification.
 - b. If the Copermitee identifies the source of the exceedance as an illicit discharge or connection, then the Copermitees consistent with Section

Deleted: Each Copermitee, beginning no later than the one year following adoption of this Order, shall implement the non-storm water dry weather action level (NAL) monitoring as described in Attachment E of this Order.

Deleted: ally influenced

Deleted: and conveyance

Deleted: fourteen

¹ During the interim, Copermitees shall continue to implement the existing Dry Weather Reconnaissance Program

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

F.4.f must eliminate or permit the discharge to their MS4 and report the findings, including any follow up and/or enforcement action(s) taken, and documentation of the source investigation to the Regional Board within thirty days. If the Copermittee is unable to eliminate or permit the source of discharge within thirty days, then the Copermittee must submit, as part of their action report, their plan and timeframe to eliminate or permit the source of the exceedance. Those dischargers seeking to continue such a discharge must become subject to a separate NPDES permit prior to continuing any such discharge. Where the source is a non-point discharge whose complete and consistent elimination is demonstrated not to be feasible, the Copermittee must submit their plan for ongoing control programs and numeric measurements of progress, with status reports to be submitted annually.

Deleted: fourteen

Deleted: of the source identification

Deleted: fourteen

Formatted: Font: Not Italic

c. If the Copermittee identifies the source of the exceedance as an exempted category of non-storm water discharges, then the Copermittees must determine if this is an isolated circumstance or if the category of discharges must be addressed through the prevention or prohibition that category of discharge as an illicit discharge. The Copermittee must submit their findings including a description of the steps taken to address the discharge or the category of discharge, to the Regional Board with the next subsequent annual report or thirty days, whichever is later. Such description shall include relevant updates to or new ordinances, orders, or other legal means of addressing the category of discharges. The Copermittees must also submit a summary of their findings with the Report of Waste Discharge.

Deleted: subsequently

d. If the Copermittee identifies the source of the exceedance as a non-storm water discharge in violation or potential violation of an existing separate NPDES permit (e.g. the groundwater dewatering permit), then the Copermittee must report, within five business days, the findings to the Regional Board including all pertinent information regarding the discharger.

Deleted: three

e. If the Copermittee is unable to identify the source of the exceedance after taking and documenting reasonable steps to do so, then the Copermittee must identify the pollutant as a high priority pollutant of concern in the tributary subwatershed, perform additional focused sampling and update their programs within a year to reflect this priority. The Copermittee's annual report shall include these updates to their program including, where applicable, updates to their watershed workplans (Section G.2), retrofitting consideration (Section F.3.d) and/or program effectiveness work plans (Section J.4).

f. If any Copermittee identifies a significant number of exceedances of NALs that prevent them from adequately conducting source investigations in a timely manner, then the Copermittees may submit a prioritization plan and timeline that

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

identifies the timeframe and planned actions to investigate and report their findings on all of the exceedances.

4. An exceedance of an NAL does not alone constitute a violation of the provisions of this Order, however, an exceedance of an NAL may indicate that the Copermittees need to do more to meet the requirement to effectively prohibit unauthorized non-storm water discharges into the MS4 or other prohibitions set forth in Sections A and B of this Order. Failure to timely implement required actions specified in this Order following an exceedance of an NAL constitutes a violation of this Order. However, neither compliance with NALs nor compliance with required actions following observed exceedances, relieves the Copermittees from the requirement to effectively prohibit all types of unauthorized non-storm water discharges into the MS4s or any non-compliance with the prohibitions in Sections A and B of this Order. During any annual reporting period in which one or more exceedances of NALs have been documented the Copermittee must submit with their next scheduled annual report, a report describing whether and how the observed exceedances did or did not result in a discharge from the MS4 that caused, or threatened to cause or contribute to a condition of pollution, contamination, or nuisance in the receiving water.

Deleted: 3
Deleted: but
Deleted: maycould
Deleted: lack of compliance with the requirement
Deleted: may
Deleted: all types of

Deleted: excuses any non-compliance with

5. Monitoring of effluent will occur at the end-of-pipe prior to discharge into the receiving waters, with a focus on Major Outfalls, as defined in 40 CFR 122.26(B 5-6) and Attachment E of this Order. The Copermittees must develop their monitoring plans to sample a representative percentage of major outfalls and identified stations within each hydrologic subarea. At a minimum outfalls that exceed any NALs once during any year must be monitored in the subsequent year unless the likely and expected cause of the exceedance is not anthropogenic in nature and is documented in accordance with paragraph C2.a; or the discharge is demonstrated not to cause or contribute to a condition of pollution, contamination, or nuisance in the receiving water. Any station that does not exceed any NALs for 3 years may be replaced with a different station.

Deleted: 4

Formatted: Font: Not Italic
Formatted: Font: Not Italic

6. If the Copermittees fail to submit the NALs and implementation plan within 18 months of the Order effective date pursuant to C.1, then the default non-storm water dry weather action levels shall be the water quality objectives contained within the Basin Plan or Ocean Plan as applicable for the following constituents:

Deleted: 5

Discharges to Inland Surface Waters

- | | | |
|---------------------------|---|-----------------------------------|
| • <u>Fecal coliform</u> | • <u>Total Phosphorous</u> | • <u>Chromium VI (hexavalent)</u> |
| • <u>Enterococci</u> | • <u>Methylene Blue Active Substances</u> | • <u>Lead</u> |
| • <u>Turbidity</u> | • <u>Cadmium</u> | • <u>Nickel</u> |
| • <u>pH</u> | • <u>Copper</u> | • <u>Silver</u> |
| • <u>Dissolved oxygen</u> | • <u>Chromium III</u> | • <u>Zinc</u> |
| • <u>Total Nitrogen</u> | | |

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

Discharges to bays, harbors, and lagoons/estuaries

- Total coliform
- Fecal coliform
- Enterococci
- Turbidity
- pH
- Priority pollutants

Discharges to the surf zone

- Total coliform
- Fecal coliform
- Enterococci

[BASIN PLAN OR OCEAN PLAN OBJECTIVES TO BE INSERTED]

Pg. 71, Section F.4.e. Illicit Discharge Detection and Elimination; Investigation/Inspection and Follow-Up:

Each Copermittee must implement procedures to investigate and inspect portions of the MS4 that, based on the results of field screening, analytical monitoring, or other appropriate information, indicate a reasonable potential of containing illicit discharges, illicit connections, or other sources of pollutants in non-storm water.

(1) Develop response criteria for data: Each Copermittee must develop, update, and use numeric criteria action levels (or other actions level criteria where appropriate) to determine when follow-up investigations will be performed in response to water quality monitoring. The criteria must include non-storm water action levels (see Section C) and a consideration of 303(d)-listed waterbodies and environmentally sensitive areas (ESAs) as defined in Attachment C.

Attachment E: Monitoring and Reporting

Pg. 12, C. Non-Storm Water Dry Weather Action Levels

Each Copermittee must collaborate with the other Copermittees to conduct, and report on a year-round watershed based Dry Weather Non-storm Water MS4 Discharge Monitoring Program. The monitoring program implementation, analysis, assessment, and reporting must be conducted on a watershed basis for each of the hydrologic units. The monitoring program must be designed to identify unauthorized non-storm water discharges through the use of non-storm water dry weather action levels in section C of this Order, adopted dry weather Total Maximum Daily Loads Waste Load Allocations and assessment of the contribution of dry weather flows to 303(d) listed impairments. The monitoring program must include the following components;

Each Copermittee's program must be designed to determine levels of pollutants in effluent discharges from the MS4 into receiving waters. Each Copermittee must conduct the following dry weather field screening and analytical monitoring tasks:

Formatted

Formatted

Deleted: Each Copermittee shall monitor for the non-storm water dry weather action levels, which are incorporated into this Order as follows:
a. Action levels for discharges to inland surface waters:
The NALs for Cadmium, Copper, Chromium (III), Lead, Nickel, Silver and Zinc will be developed on a case-by-case basis because the freshwater criteria are based on site-specific water quality data (receiving water hardness). For these priority pollutants, the following equations (40 CFR 131.38.b.2) will be required:

Deleted: Cadmium (Total Recoverable) ... [1]

Formatted: Not Highlight

Deleted: assess compliance with

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

a. Dry Weather Non-storm Water Effluent Analytical Monitoring Stations

- (1) Stations must be major outfalls. Major outfalls chosen must include outfalls discharging to inland surface waters; to bays, harbors and lagoons/estuaries; and to the surf zone. Other outfall points (or any other point of access such as manholes) identified by the Copermittees as potential high risk sources of polluted effluent or as identified under Section C.3.e shall be sampled.
- (2) Each Copermittee must clearly identify each dry weather' effluent analytical monitoring station on its MS4 Map as either a separate GIS layer or a map overlay hereafter referred to as a Dry Weather Non-storm Water Effluent Analytical Stations Map.

b. Develop Dry Weather Non-storm Water Effluent Analytical Monitoring Procedures

Each Copermittee must develop and/or update written procedures for effluent analytical monitoring (these procedures must be consistent with 40 CFR part 136), including field observations, monitoring, and analyses to be conducted. At a minimum, the procedures must meet the following guidelines and criteria:

- (1) Determining Sampling Frequency: Effluent analytical monitoring must be conducted at major outfalls and identified stations. The Copermittees must sample a representative number of major outfalls and identified stations. The sampling must be done to assess exceedances of the dry weather non-storm water action levels pursuant to section C of this Order. All monitoring conducted must be preceded by a minimum of 72 hours of dry weather.
- (2) If ponded MS4 discharge is observed at a monitoring station, make observations and collect at least one (1) grab sample. If flow is evident a 1 hour composite sample may be taken. Record flow estimation (i.e., width of water surface, approximate depth of water, approximate flow velocity, flow rate).
- (3) Effluent samples shall undergo analytical laboratory analysis for constituents in: *Table 1. Analytical Testing for Mass Loading, Urban Stream Bioassessment, and Ambient Coastal Receiving Waters Stations* and for those constituents with action levels under Section C of this Order. Effluent samples must also undergo analysis for Chloride, Sulfate and Total Dissolved Solids.
- (4) If the station is dry (no flowing or ponded MS4 discharge), make and record all applicable observations.

Deleted: compliance with

Formatted: Position: Horizontal:
4.17", Relative to: Page, Vertical: 0",
Relative to: Paragraph

- (5) Develop and/or update criteria for dry weather non-storm water effluent analytical monitoring:
 - (a) Criteria must include action levels in Section C of this Order.hk
 - (b) Criteria must include evaluation of LC₅₀ levels for toxicity to appropriate test organisms
- (6) Develop and/or update procedures for source identification follow up investigations in the event of exceedances of dry weather non-storm water action level analytical monitoring result criteria. These procedures must be consistent with procedures required in section F.4.d and F.4.e. of this Order.
- (7) Develop and/or update procedures to eliminate detected illicit discharges and connections. These procedures must be consistent with the non-storm water dry weather action levels in section C and with each Copermitees' Illicit Discharge and Elimination component of its Jurisdictional Runoff Management Plan as discussed in section F.4 and F.4.e. of this Order.

Deleted: effluent

c. Conduct Dry Weather Non-storm Water Effluent Analytical Monitoring

The Copermitees must commence implementation of dry weather effluent analytical monitoring under the requirements of this Order no later than one year following adoption of this Order. If monitoring indicates an illicit connection or illegal discharge, conduct the follow-up investigation and elimination activities as described in submitted dry weather field screening and analytical monitoring procedures and found in sections C.F.4.d and F.4.e of Order No. R9-2009-0002.

Until the dry weather non-storm water effluent analytical monitoring program is implemented under the requirements of this Order, each Copermitee must continue to implement dry weather field screening and analytical monitoring as it was most recently implemented pursuant to Order No. 2002-01.

Attachment F – Source Data
Page 1 and 9,

II. NON-STORM WATER ACTION LEVELS

Formatted: Position: Horizontal:
4.17", Relative to: Page, Vertical: 0",
Relative to: Paragraph

Tentative Order Fact Sheet

Page 20, Discussion on Finding A.1:

As a means for achieving those water quality objectives, Porter-Cologne (section 13243) further authorizes the Regional Water Quality Control Boards to establish waste discharge requirements (WDRs) to prohibit waste discharges in certain conditions or areas. Since 1990, the San Diego Regional Board has issued area-wide MS4 NPDES permits. The Order will renew Order No. R9-2002-01 to comply with the CWA and attain water quality objectives in the Basin Plan by limiting the contributions of pollutants conveyed by storm water and by including numeric action levels for dry weather non-storm water discharges designed to ensure that the Copermitees comply with the requirement to effectively prohibit unauthorized non-storm water discharges into their MS4s. Further discussions of the legal authority associated with the prohibitions and directives of the Order are provided in section VII this document.

Deleted: all types of

Page 45, Discussion on Finding C.14:

As explained in the discussion of Finding C.15., below, the Copermitees' reliance on BMPs for the past 19 years has not resulted in compliance with applicable water quality standards. The Regional Board has evaluated (in accordance with 40 CFR 122.44(d)(1)) past and existing controls (BMPs), non-storm water effluent monitoring results, the sensitivity of the species in receiving waters (e.g. endangered species), and the potential for effluent dilution, and has determined that existing BMPs to control pollutants in storm water discharges are not sufficient to protect water quality standards in receiving waters and the existing requirement that Copermitees effectively prohibit unauthorized non-storm water discharges into the MS4 historically results in the discharge of pollutants to the receiving waters. Thus, numeric action levels for non-storm water, dry weather, discharges from the MS4 and required actions following observed exceedances of numeric action levels have been established. For further discussion regarding the development of action levels please see Finding E.12 and discussion.

Deleted: all types of

Dry weather action levels are applicable to non-storm water discharges of effluent from the MS4 system. Non-storm water effluent discharges from the MS4 are those which occur during dry weather conditions. These action levels are not applied to storm water discharges, as defined within the Order. Storm water discharges regulated by the Order are required to meet the MEP standard and related iterative process and have separate action levels.

Dry weather action levels are applicable to non-storm water discharges from the MS4 system into receiving waters. Non-storm water discharges are already required to be prohibited unless specifically exempted or covered under a separate NPDES permit. Dry weather action levels apply to non-storm water discharges of effluent from a point source into receiving waters. The MS4 is not a receiving water. Should a discharger wish to discharge a non-exempt category to the MS4 system, such discharges require a separate NPDES permit pursuant to sections 402 and 301 of the CWA. It is also

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

infeasible to monitor and sample every discharge into the MS4, as such discharges are diffuse by nature and may vary spatially and temporally.

Finding E.12 This Order requires each Copermitttee to effectively prohibit unauthorized non-storm water discharges into its MS4. However, pollutants have been identified in dry weather non-storm water discharges from the MS4s through 303(d) listings, and monitoring conducted by the Copermitttees under Order No. R9-2002-0001. This Order includes action levels for pollutants in non-storm water, dry weather, discharges from the MS4 designed to assist in determining if the requirement to effectively prohibit unauthorized discharges of non-storm water in the MS4 is being met. Action levels in the Order are based upon numeric or narrative water quality objectives and criteria as defined in the Basin Plan, and the Water Quality Control Plan for Ocean Waters of California (Ocean Plan). An exceedance of an action level requires a specified responsive action by the Copermitttees. This Order describes what actions the Copermitttees must take when an exceedance of an action level is observed. Exceedances of non-storm water action levels do not constitute a violation of this Order, however, it could indicate that the Copermitttee may need to do more to meet the requirement to effectively prohibit unauthorized non-storm water discharges into the MS4 or other prohibitions established in this Order. Failure to undertake the required responsive actions such as source investigations and/or elimination actions following an exceedance of a non-storm water action level (NAL or action level) is a violation of this Order. Establishing NALs at levels appropriate to protect water quality standards is expected to lead to the identification of significant sources of pollutants in dry weather non-storm water discharges.

Discussion of Finding E.12. This Order includes the existing requirement that Copermitttees effectively prohibit unauthorized non-storm water discharges in the MS4s. It also includes the following prohibition set forth in the Basin Plan: "The discharge of waste to waters of the state in a manner causing, or threatening to cause a condition of pollution, contamination or nuisance as defined in California Water Code section 13050 is prohibited." (Prohibition A.1.) As discussed in the Order's Findings on discharge characteristics, e.g., C.2., C.4., C.6., C.7., C.9., C.14., and C.15., the Copermitttee's reliance on BMPs for the past 19 years has not resulted in compliance with applicable water quality standards or compliance with the requirement to effectively prohibit unauthorized discharges of non-storm water in the MS4. The Regional Board has evaluated (in accordance with 40 CFR 122.44(d)(1)) past and existing control (BMPs), non-storm water effluent monitoring results, the sensitivity of the species in receiving waters (e.g. . endangered species), and the potential for effluent dilution and has determined that existing BMPs to control pollutants in storm water discharges are not sufficient to protect water quality standards in receiving waters and the existing requirement that Copermitttees effectively prohibit unauthorized non-storm water discharges into the MS4 historically results in the discharge of pollutants to the receiving waters.

It is appropriate to establish dry weather non-storm water action levels protective of water quality standards to measure pollutants levels in the discharge of dry weather non-storm water that could indicate non-compliance with the requirement to effectively

- ~~Deleted: all types of~~
- ~~Deleted: of non-storm water~~
- ~~Deleted: historically~~
- ~~Deleted: as present~~
- ~~Deleted: , and there are others expected to be present in dry weather non-storm water discharges because of the nature of these discharges~~
- ~~Deleted: ensure that~~
- ~~Deleted: all types of~~
- ~~Deleted: complied with~~
- ~~Deleted: , and the State Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (State Implementation Policy or SIP)~~
- ~~Deleted: alone~~
- ~~Deleted: but~~
- ~~Deleted: non-compliance with~~
- ~~Deleted: all types of~~
- ~~Deleted: n~~
- ~~Deleted: The Regional Board recognizes that use of action levels will not necessarily result in detection of all unauthorized sources of non-storm water discharges because there may be some discharges in which pollutants do not exceed established action levels. However, e~~
- ~~Deleted: all types of~~

~~Deleted: all types of~~

~~Deleted: all types of~~

- ~~Deleted: Therefore i~~
- ~~Deleted: based upon established~~
- ~~Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph~~

prohibit unauthorized non-storm water discharges into the MS4 and/or that these discharges are causing, or threatening to cause, a condition of pollution, contamination or nuisance in the receiving waters. NALs are not numeric effluent limitations. An exceedance of an NAL requires the Copermittees to initiate a series of source investigations and/or elimination actions to address the exceedance. Results from the NAL monitoring are to be used in developing the Copermittees annual work plans. Failure to undertake required source investigation and/or elimination actions in a timely manner following an exceedance of an NAL is a violation of this Order. Please see further discussion in the directives section C of the fact sheet.

Deleted: all types of

Deleted: While not alone a violation of this Order a

A purpose of monitoring, required under this and previous Orders, as stated in the Monitoring and Reporting Program is to "detect and eliminate illicit discharges and illicit connections to the MS4" and to answer the following core management questions:

1. Are conditions in receiving waters protective, or likely to be protective, of beneficial uses?
2. What is the extent and magnitude of the current or potential receiving water problems?
3. What is the relative MS4 discharge contribution to the receiving water problem(s)?
4. What are the sources of MS4 discharge that contribute to receiving water problem(s)?
5. Are conditions in receiving waters getting better or worse?

For the past 4 permit cycles (19 years), Copermittees have utilized their IC/ID program to identify and eliminate non-storm water discharges that are sources of pollutants to the MS4. The Copermittees are also subject to the requirement to effectively prohibit unauthorized discharges of non-storm water into the MS4s. Historically, discharges of unauthorized non-storm water do occur, resulting in the discharge of pollutants to the receiving waters. NALs have been included in this Order to assist the Copermittees in complying with the requirement to effectively prohibit unauthorized non-storm water discharges that are a source of pollutants in the receiving waters.

Deleted: all types of

Deleted: ensure that

Deleted:

Deleted: all types of

Page 106

C. Non Storm Water Dry Weather Action Levels

The following legal authority applies to Section C:

Broad Legal Authority: CWA section 402, 402(p)(3)(B)(ii), CWC §13377, 40 CFR 122.26(d)(2)(i)(B, C, E, and F), and 40 CFR 122.26(d)(2)(iv).

Specific Legal Authority:

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

The Clean Water Act section 402(p)(3)(B)(ii) provides that MS4 permits "shall include a requirement to effectively prohibit non-storm water discharges into the storm sewers."

Federal NPDES regulations 40 CFR 122.26(d)(2)(iv)(B) provides that the proposed management program "shall be based on a description of a program, including a schedule, to detect and remove (or require the discharger to the municipal storm sewer to obtain a separate NPDES permit for) illicit discharges and improper disposal into the storm sewer."

Federal NPDES regulation 40 CFR 122.26(d)(2)(iv)(B)(1) provides that the Copermitee include in its proposed management program "a program, including inspections, to implement and enforce an ordinance, orders or similar means to prevent illicit discharges to the municipal storm sewer system; this program description shall address all types of illicit discharges, however the [listed exempt] category of non-storm water discharges or flows shall be addressed where such discharges are identified by the municipality as sources of pollutants to waters of the United States."

Federal NPDES regulation 40 CFR 122.26(d)(2)(iv)(B)(2) provides that the Copermitee include in its proposed management program "a description of procedures to conduct on-going field screening activities during the life of the permit, including areas or locations that will be evaluated by such field screens."

Federal NPDES regulation 40 CFR 122.26(d)(2)(iv)(B)(3) provides that the Copermitee include in its proposed management program "procedures to be followed to investigate portions of the separate storm sewer system that, based on the results of the field screen, or other appropriate information, indicate a reasonable potential of containing illicit discharges or other sources of non-storm water."

Section C establishes non-storm water dry weather action levels (see also Finding C.14, Finding E.12 and the Discussion for those sections).

Non-exempted, non-storm water discharges are to be effectively prohibited from entering the MS4 or become subject to another NPDES permit (see Federal Register, Vol. 55, No. 222, pg. 47995). Conveyances which continue to accept non-exempt, non-storm water discharges do not meet the definition of MS4 and are not subject to section 402(p)(3)(B) of the CWA unless the discharges are issued separate NPDES permits. Instead, conveyances that continue to accept non-exempt, non-storm water discharges that do not have a separate NPDES permit are subject to sections 301 and 402 of the CWA (see Federal Register, Vol. 55, No. 222, pg. 48037).

The Order requires the sampling of a representative percentage of major outfalls and other identified stations within each hydrologic subarea. While it is important to assess all major outfall discharges from the MS4 into receiving waters, to date the Copermitees have implemented a dry-weather monitoring program that has identified major outfalls that are representative of each hydrologic subarea and have randomly sampled other major outfalls. Thus, it is expected that the Copermitees will utilize past

Formatted: Position: Horizontal:
4.17", Relative to: Page, Vertical: 0",
Relative to: Paragraph

dry weather monitoring in the selection and annual sampling of a representative percentage of major outfalls in accordance with the requirements under Section C.4.

Background and Rationale for Requirements

The Regional Board developed the requirements for dry weather non-storm water action levels based upon an evaluation of existing controls, monitoring and reporting programs (effluent and receiving water), special studies, and based upon Findings C.1 C.3, C.4, C.6, C.7 and C.14.

Water Quality Control Plan

Section 303(C) of the Clean Water Act requires the state to establish Water Quality Standards (WQS). WQS define the water quality goals of a waterbody, or part thereof, by designating their use or uses to be made of the water and by setting criteria necessary to protect those uses.

The Regional Board's Water Quality Control Plan for the San Diego Basin (Basin Plan) designates beneficial uses, establishes water quality objectives, and contains implementation programs and policies to achieve those objectives for all waters addressed through the Basin Plan. The Basin Plan was adopted by the Regional Board on September 08, 1994, and was subsequently approved by the State Board on December 13, 1994. Subsequent revisions to the Basin Plan have also been adopted by the Regional Board and State Board.

State Board Resolution No. 88-63 establishes state policy that all waters, with certain exceptions, should be considered suitable or potentially suitable for municipal and domestic supplies. Requirements of this Order do not include effluent limitations reflecting municipal and domestic supply use as all waters within the County of Orange under this Order are specifically exempted from municipal and domestic supply as a Beneficial Use.

The State Board adopted the Water Quality Control Plan for Ocean Waters of California (Ocean Plan) in 2005, it was approved by USEPA, and became effective on February 14, 2006. The Ocean Plan establishes Water Quality Objectives, general requirements for management of waste discharged to the ocean, effluent quality requirements, discharge provisions, and general provisions. Limitations derived from the Ocean Plan have been included in this Order to protect the Beneficial Uses of enclosed bays and estuaries because their Beneficial Uses are similar

National Toxics Rule (NTR) and California Toxics Rule (CTR)

The USEPA adopted the NTR on December 22, 1992, which was amended on May 04, 1995, and November 09, 1999. The CTR was adopted by USEPA on May 18, 2000, and amended on February 13, 2001. These rules include water quality criteria for priority pollutants and are applicable to non-storm water discharges from the MS4. Criteria for 126 priority pollutants are established by the CTR. USEPA promulgated this rule to fill a gap in California water quality standards that was created in 1994 when a

Formatted: Position: Horizontal:
4.17", Relative to: Page, Vertical: 0",
Relative to: Paragraph

California court overturned the State's water quality control plans containing criteria for priority toxic pollutants. The federal criteria are legally applicable in the State of California for inland surface waters, enclosed bays and estuaries for all purposes and programs under the CWA.

Antidegradation Policy

Section 131.12 of 40 CFR requires that the State water quality standards include an antidegradation policy consistent with the federal policy. The State Board established California's antidegradation policy in State Board Resolution No. 68-16. Resolution No. 68-16 incorporates the federal antidegradation policy where the federal policy applies under federal law. Resolution No. 68-16 requires that existing quality of waters be maintained unless degradation is justified based on specific findings. The Regional Boards' Basin Plans implement, and incorporate by reference, both the State and federal antidegradation policies. Permitted non-storm water discharges from the MS4 are consistent with the antidegradation provision of 40 CFR section 131.12 and State Board Resolution No. 68-16.

Monitoring and Reporting

40 CFR Section 122.48 requires that all NPDES permits specify requirements for recording and reporting monitoring results. Sections 13267 and 13383 of CWC authorize the Regional Boards to require technical and monitoring reports. The Monitoring and Reporting Program establishes monitoring and reporting requirements to implement state and federal regulations. The Monitoring and Reporting Program can be found as Attachment E of the Order.

Dilution or Mixing Zones

In order to protect the Beneficial Uses of receiving waters from pollutants as a result of non-storm water MS4 discharges, this Order does not provide for a mixing zone or a zone of initial dilution except when the discharge is to the surf zone.

The San Diego Region has predominately intermittent and ephemeral rivers and streams (Inland Surface Waters) which vary in flow volume and duration at spatial and temporal scales. Therefore, it is assumed that any non-storm water discharge from the MS4 into the receiving water is likely to be of a quantity and duration that does not allow for dilution or mixing. For ephemeral systems, non-storm water discharges from the MS4 are likely to be the only surface flows present within the receiving water during the dry season.

MS4 discharge points to bays, estuaries and lagoons are not designed to achieve maximum initial dilution and dispersion of non-storm water discharges. Thus, initial dilution factors for non-storm water discharges from the MS4 into bays, estuaries, and lagoons are conservatively assumed to equal zero.

It is appropriate to base numeric action levels for dry weather non-storm water discharges on these considerations.

Formatted: Position: Horizontal:
4.17", Relative to: Page, Vertical: 0",
Relative to: Paragraph

California Ocean Plan

A discharge to a surf zone occurs when the non-storm water discharge point from the MS4 discharges:

- a) Directly into the ocean in a wave induced area subject to long-shore conditions; or
- b) Across a primarily sandy substrate beach and subsequently directly into a wave induced area subject to long-shore conditions;

Establishment of Action levels

Action levels in the Order are based upon numeric or narrative water quality objectives and criteria as defined in the Basin Plan and the Water Quality Control, Plan for Ocean Waters of California (Ocean Plan). The Regional Board recognizes that use of action levels will not necessarily result in detection of all unauthorized sources of non-storm water discharges because there may be some discharges in which pollutants do not exceed established action levels.

Deleted: , and the State Policy for Implementation of Toxic Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (State Implementation Policy or SIP)

In June of 2006, the California Water Board's Blue Ribbon Storm Water Panel released it's report titled 'The Feasibility of Numerical Effluent Limits Applicable to Discharges of Storm Water Associated with Municipal, Industrial and Construction Activities.' The report only examined numerical limits as applied to storm water and not non-storm water. In the recommendations, the Blue Ribbon panel proposed storm water action levels which are computed using statistical based population approaches. For example, Section D of the Permit uses a recommended statistical approach to develop storm water action levels. The Blue Ribbon panel did not examine the efficacy of action levels or recommendations for development of action levels for non-storm water discharges.

For discharges to inland surface waters, action levels are based on the EPA water quality criteria for the protection of aquatic species, the EPA water quality criteria for the protection of human health, water quality criteria and objectives in the applicable State plans, effluent concentration available using best available technology, and 40 CFR 131.38. Since the assumed initial dilution factor for the discharge is zero and a mixing zone is not allowed, a non-storm water discharge from the MS4 could not cause an excursion from numeric receiving water quality objectives if the discharge is below the action levels contained in the Order. Likewise, discharges below action levels to the surf zone cannot cause excursions from water quality objectives.

Deleted: in compliance with
Deleted: effluent
Deleted: in compliance with

Dry weather monitoring of non-storm water MS4 effluent conducted under the previous Order (R9-2002-001), which relies on BMPs as controls to protect water quality standards, has identified pollutants that are found in non-storm water discharges. Monitoring of pH, Dissolved Oxygen, Phosphorus, Nitrate, Turbidity and Methylene Blue Active Substances (MBAS) in non-storm water MS4 discharges has shown that the effluent concentrations are above state water quality criteria. Therefore, it is appropriate to establish numeric action levels for these pollutants to assist the Copermittees in

Deleted: exceeds
Deleted: |
Deleted: numeric the effluent exceeds state water quality criteria
Deleted: ensure that
Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

meeting the requirement to effectively prohibit unauthorized non-storm water discharges into the MS4s.

Deleted: are complying with

Deleted: all types of

Water Quality Limited Segments on the current 303(d) list (2006) within the jurisdiction of this Order have been identified due to exceedances of Sulfate, Chloride and Total Dissolved Solids criteria from a source which is currently unknown (see Table 2a). These pollutants are not monitored for under the current non-storm water MS4 effluent monitoring program. This Order now requires non-storm water MS4 discharge monitoring to include monitoring for Sulfates, Chlorides and Total Dissolved Solids.

Priority pollutants analyzed included Cadmium, Copper, Chromium, Lead, Nickel, Silver and Zinc. These priority pollutants are likely to be present in non-storm water MS4 discharges (see Finding C.3) and dissolved metal effluent monitoring is available from the previous Order. The most stringent applicable water quality criteria have been identified for these seven metals and, excluding Chromium (VI), and all are dependent on receiving water hardness. The conversion factors for Cadmium and Lead are also water hardness dependent (40 CFR 131.38(b)(2)). These levels are established as the action levels for these constituents.

While effluent monitoring is available from the previous Order, the monitoring was done for dissolved concentrations and lacked a measurement of receiving water hardness. Due to the multiple point source discharges of non-storm water from the MS4, a discharge may enter a receiving water whose hardness will vary temporally. In addition, hardness may vary spatially within and among receiving waters.

However, other information is available to determine the appropriateness of an action level. Existing effluent monitoring concentrations absent of receiving water data, no dilution credit or mixing zone allowance, current 303(d) listings of receiving waters for other pollutants, receiving water monitoring data, and the classification of waters as critical habitat for endangered and species of concern, provide evidence that NALs are appropriate for these priority pollutants at this time in order to assist the Copermitttees in meeting the requirement to effectively prohibit unauthorized non-storm water discharges into the MS4s.

Deleted: ensure that

Deleted: comply with

Deleted: all types of

Existing effluent data (see attachment F), absent receiving water hardness, provides evidence that it is appropriate to include NALs based on a conservative hardness level. Absent receiving water hardness, all analyzed metals, are discharged at concentrations which may be in exceedance of CTR criteria depending on receiving water hardness. Chromium effluent data that is available is in the form of total Chromium. However, Chromium criteria are for Chromium III and Chromium VI. Therefore, the total Chromium measurement is inadequate, but can be used as an estimate of Chromium III and VI concentrations.

Deleted: per the SIP,

As discussed, inland surface waters, enclosed bays, and estuaries have conservatively been allotted a mixing zone and dilution credit of zero. As discussed in Finding C.7 and discussion, multiple receiving waters within the County of Orange are 303(d) listed for a number of pollutants, including toxicity. The 303(d) listing of a waterbody as impaired

Deleted: As such, any discharge of these priority pollutants is likely to impact the receiving water, regardless of the quantity or rate of discharge.¶

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

provides evidence that the receiving water(s) are already experiencing negative impacts. These water quality limited segments are more susceptible to degradation from the synergistic addition of more pollutants, even from upstream discharges. It is therefore appropriate to include numeric action levels designed to ensure that the Copermittees are complying with the requirement to effectively prohibit unauthorized discharges of non-storm water into the MS4s.

Deleted: all types of

Copermittees have monitored the receiving waters for MS4 discharges pursuant to requirements under Order R9-2002-0002. Dry weather receiving water data indicates poor conditions within waters receiving non-storm water MS4 discharges. Urban stream bioassessment conducted under the Order (2002-2008) has documented all non-reference sites as consistently having poor or very poor Index of Biotic Integrity (IBI) scores, in part due to receiving water toxicity.²

Receiving waters within the jurisdiction of this Order are classified as critical habitat, including being designated with the RARE beneficial use, for endangered, threatened and species of concern including, but not limited to, *O. mykiss irideus*, *E. newberryii*, *A. marmorata pallida* and *G. orcutti*.

The Regional Board evaluated discharges to the surf zone per the California Ocean Plan, Appendix VI and in accordance with 40 CFR 122.44(d). Indicator bacteria, pH, turbidity (NTU), and metals were analyzed for the purpose of determining the levels of these constituents in non-storm water discharges from the MS4.

The Regional Board has determined that there is not sufficient information at this time to develop action levels for pH, turbidity and metals. While non-storm water MS4 effluent data is available, the data collected is for discharges to inland surface waters, enclosed bays and estuaries. Preliminary receiving water data and limited non-storm water MS4 discharge data collected under the Ambient Coastal Receiving Water Monitoring indicates some exceedances of criteria for metals in the discharge, and toxicity in receiving waters³. However, the Regional Board believes the level of data available is insufficient, and is requiring additional monitoring of pH, turbidity and metals in non-storm water MS4 discharges to ocean waters (discharges to the surf zone).

Water Quality Limited Segments on the current 303(d) list (2006) for the Pacific Ocean shoreline within the jurisdiction of this Order have been identified due to exceedances of Indicator Bacteria criteria whose known source includes non-storm water discharges from the MS4. These 303(d) listed segments support extensive REC-1 beneficial uses and are located within State Marine Reserves and Conservation Areas. The listing of receiving waters as 303(d) listed for bacteria supports the inclusion of action levels to ensure that the Copermittees are complying with the requirement to effectively prohibit all types of unauthorized non-storm water discharges into the MS4. In addition, no dilution credit or mixing zone allowance is included in developing numeric action levels for the discharge of a pollutant to waters which are 303(d) as impaired for that pollutant.

² 2006-07 and 2007-08 Unified Annual Progress Reports.

³ 2007-08 Unified Annual Progress Report.

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

Compliance with Permit,

Compliance with Section C shall be determined as follows:

Dischargers shall be deemed to be out of compliance with this Order if the Copermittee failed to take the prescribed responsive actions in response to an exceedance of a numeric action level. ~~Regardless of the Copermittee's actions in response to an exceedance, they are still subject to the prohibitions found in Sections A and B of the Order.~~

When determining to take an action in response to the NALs and more than one sample result is available in a month, the discharger shall consider the frequency, magnitude, and number of constituents exceeding the NALs.

Page 155, Section F.4.e. Illicit Discharge Detection and Elimination (Investigations)

The Copermittees currently use action levels to facilitate the determination of when source investigation studies are warranted based on data from the dry-weather monitoring program. One set of criteria is based on regional averages of constituent concentrations that were developed based on randomly selected storm drains. Another set of criteria is based on trends at a particular station. These are reasonable criteria if decision-makers are properly trained and action levels set by the County are in compliance with dry weather non-storm water action levels as required in Section C. The ability of the local managers to interpret dry-weather monitoring data collected by the County has greatly improved in the last two years, and continued training is required in section F.4.i.

Page 178, Section T. Attachment E – Receiving Waters and MS4 Discharge Monitoring and Reporting Program

Considering the benefits described above, the Receiving Waters Monitoring and Reporting Program (MRP) has been designed to determine impacts to receiving water quality and beneficial uses from storm water runoff and to use the results to refine the Copermittees' storm water runoff management programs for the reduction of storm water pollutant loadings to the MEP. For non-storm water discharges, monitoring has been designed for the identification of prohibited illicit discharges and to determine appropriate actions to take in response to dry weather non-storm water action levels. Additionally, the results from dry weather non-storm water monitoring can be used to evaluate exempted non-storm water discharges as a source or conveyance of pollutants. The primary goals of the MRP include:

Page 186,

Dry Weather Non-storm Water Action Levels

~~Deleted: Calculations for Discharges to Inland Surface Waters, Enclosed Bays, and Estuaries.~~

~~On the basis of the foregoing discussion, the NALs were calculated with the following considerations and assumptions:~~

~~No dilution credit is considered for the discharge. Therefore, the discharge must comply with the Water Quality Objective at the point of discharge.~~

~~For NALs based on CTR, implementation was done using the procedure list as outlined in the SIP (see below example).~~

~~NAL CTR/SIP Calculation – Zinc Example:~~

~~Criteria for Priority Toxic Pollutants in the State of California is described in the CTR table listed in 40 CFR 131.38.~~

~~Insert Table:~~

~~These criteria are expressed in terms of the dissolved fraction of the metal in the water column. [See footnote "m" to Table in paragraph (b)(1) of 40 CFR 131.38].~~

~~40 CFR 122.45(c) requires that this Order include effluent limitations as total recoverable concentration; therefore it is appropriate to include action levels also as total recoverable concentration.~~

~~The SIP requires that if it is necessary to express a dissolved metal value as a total recoverable and a site-specific translator has not yet been developed, the Regional Board shall use the applicable conversion factor from 40 CFR 131.38.~~

~~The term "Conversion Factor" (CF) represents the recommended conversion factor for converting a metal criterion expressed as th~~ ... [2]

~~Deleted: Action levels (Priority Pollutants)~~

~~Deleted: action levels~~

~~Deleted: concentration of the priority pollutant in the monitoring sample that is greater than the action level and greater than or equal to the reported Minimum Level (~~

~~Deleted:)~~

~~Deleted: AMALS~~

~~Deleted: compute the arithmetic mean unless the data set contains one or more reported determinations of DNQ or ND. In those cases, the discharger shall compute the median in place of the arithmetic mean in accordance with the following procedure:~~ ... [3]

~~Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph~~

Section II.C of the MRP describes the monitoring to be conducted by the Copermittees to determine exceedances of dry weather non-storm water action levels.

Deleted: compliance with

Section II.B.3 has been changed by removal of the Dry Weather Field Screening and Analytical Monitoring and subsequent replacement with section II.C for Dry Weather Non-Storm Water Action Level Monitoring.

This change is required to assess exceedances of action levels for non-storm water discharges from the MS4 into receiving waters. The required sampling frequency has been changed to allow Copermittees to sample a representative number of discharge points and the sampling methodology has been changed to grab sampling. This is expected to allow Copermittees to maintain a cost-neutral dry weather monitoring program that is similar to their existing IC/ID monitoring program.

Deleted: compliance

Deleted: with

Page 189, U. Attachment F – Source Data

Attachment F contains data utilized for the development of Storm Water Action Levels and Non-storm Water Action Levels.

Formatted: Position: Horizontal: 4.17", Relative to: Page, Vertical: 0", Relative to: Paragraph

Page 5: [1] Deleted	Author
Cadmium (Total Recoverable)	= exp(0.7852[in(hardness)] - 2.715)
Chromium III (Total Recoverable)	= exp(0.8190[in(hardness)] + 6848)
Copper (Total Recoverable)	= exp(0.8545[in(hardness)] - 1.702)
Lead (Total Recoverable)	= exp (1.273[in(hardness)] - 4.705)
Nickel (Total Recoverable)	= exp (.8460[in(hardness)] + 0.0584)
Silver (Total Recoverable)	= exp (1.72[in(hardness)] - 6.52)
Zinc (Total Recoverable)	= exp (0.8473[in(hardness)] + 0.884)

b. Action levels for discharges to bays, harbors and lagoons/estuaries:

Insert Table 4.b: General Constituents

c. Action levels for discharges to the surf zone:

Insert Table 4.c: General Constituents

Page 17: [2] Deleted	Author
<u>Calculations for Discharges to Inland Surface Waters, Enclosed Bays, and Estuaries.</u>	

On the basis of the foregoing discussion, the NALs were calculated with the following considerations and assumptions:

No dilution credit is considered for the discharge. Therefore, the discharge must comply with the Water Quality Objective at the point of discharge.

For NALs based on CTR, implementation was done using the procedure list as outlined in the SIP (see below example).

NAL CTR/SIP Calculation – Zinc Example:

Criteria for Priority Toxic Pollutants in the State of California is described in the CTR table listed in 40 CFR 131.38.

Insert Table

These criteria are expressed in terms of the dissolved fraction of the metal in the water column. [See footnote “m” to Table in paragraph (b)(1) of 40 CFR 131.38].

40 CFR 122.45(c) requires that this Order include effluent limitations as total recoverable concentration; therefore it is appropriate to include action levels also as total recoverable concentration.

The SIP requires that if it is necessary to express a dissolved metal value as a total recoverable and a site-specific translator has not yet been developed, the Regional Board shall use the applicable conversion factor from 40 CFR 131.38.

The term "Conversion Factor" (CF) represents the recommended conversion factor for converting a metal criterion expressed as the total recoverable fraction in the water column to a criterion expressed as the dissolved fraction in the water column.

Total recoverable concentration * CF = Dissolved concentration criterion

or

Total recoverable concentration = Dissolved concentration criterion/ CF

Insert Table

Effluent Variability multiplier and Coefficient of Variation (CV)

For each concentration based on an aquatic life criterion, the long-term average (LTA) is calculated by multiplying the concentration with a factor that adjusts for effluent variability. The multiplier can be found in Table 1 of the SIP. Since this Order does not have existing data to properly conduct a variability analysis in accordance with the SIP, the CV has been set equal to 0.6 per SIP requirements. The current effluent data is limited due to the small number of representative outfalls sampled, the lack of outfalls discharging to representative waterbodies within the Region, and the targeted nature of the sampling design.

Based upon a CV of 0.6, Table 1 of the SIP requires an effluent variability as follows:

Acute Multiplier = 0.321

Chronic Multiplier = 0.527

The long-term average (LTA) is calculated by multiplying the total recoverable concentrations for zinc with the acute and chronic multipliers:

LTA Acute = 95 ug/L * 0.321 = 30.5

LTA Chronic = 86 ug/L * 0.527 = 45.3

The MDAL and AMAL will be based on the most limiting of the acute and chronic LTA, in the case for copper the most limiting LTA is the acute of 30.5 ug/L

NALs are calculated by multiplying the most limiting LTA with a multiplier that adjusts for the averaging periods and exceedance frequencies of the criteria and the effluent limitations. The multiplier can be found in Table 2 of the SIP. Since

this Order has insufficient data, the CV has been set to 0.6 and since sampling frequency is four times a month or less, n has been set equal to 4 per the SIP.

Insert Table 2.

Therefore, from Table 2 of the SIP, the LTA multipliers will be as follows:

MDAL Multiplier = 3.11

AMAL Multiplier = 1.55

The MDAL and AMAL limits are calculated by multiplying the LTA with an LTA multiplier for each limit:

MDAL = 30.5 ug/L * 3.11 = 95 ug/L

AMAL = 30.5 ug/L * 1.55 = 47 ug/L

Calculations for Discharges to the Surf Zone

The Average Monthly and Maximum Daily NALs were calculated with the following considerations and assumptions:

No dilution credit is considered for the discharge. Therefore, the discharge must comply with the Water Quality Objective at the point of discharge. Whole Effluent Toxicity (WET) Testing Requirements

A WET limit is required if a discharge causes, has a reasonable potential to cause, or contributes to an exceedance of applicable water quality standards, including numeric and narrative. Since these types of discharges are prohibited under this Order, WET limits are not applicable.

Discussion of AMALs, MDALs and Instantaneous Maximums

Where practical, action levels in this Order have been expressed as both AMALs and MDALs. Certain action levels may not practicably be expressed as AMALs and MDALs due to specific BPO language, sampling requirements and/or a lack of Criteria. Based upon the likely sampling frequency of the Copermittees, the frequency of sampling will occur such that grab samples are taken once per sampling day. This single sample would then be subject to MDALs and Instantaneous Maximum levels. In this case, the more conservative action level would apply. In addition, it is expected that some effluent monitoring will occur less than or equal to once per month. In this scenario, the MDAL, AMAL and Instantaneous Maximum levels would need to be met based upon one sample, unless sampling did not occur. For some BPOs, AMALs have been excluded and only MDALs/Instantaneous Maximums set to prevent redundancy in action levels.

compute the arithmetic mean unless the data set contains one or more reported determinations of DNQ or ND. In those cases, the discharger shall compute the median in place of the arithmetic mean in accordance with the following procedure:

- (1) The data set shall be ranked from low to high, reported ND determinations lowest, DNQ determinations next, followed by quantified values (if any). The order of the individual ND or DNQ determinations is unimportant.
- (2) The median value of the data set shall be determined. If the data set has an odd number of data points then the median is the middle value. If the data set has an even number of data points, then the median is the average of the two values around the middle unless one or both of those points are ND or DNQ, in which case the median value shall be the lower of the two data points where DNQ is lower than a value and ND is lower than DNQ.

**California Regional Water Quality Control Board
San Diego Region**

**Waste Discharge Requirements for
Discharges of Runoff from the
Municipal Separate Storm Sewer Systems
(MS4s)**

**Draining the Watershed of the County of Orange,
The Incorporated Cities of Orange County, and
The Orange County Flood Control District
Within the San Diego Region**

**Order No. R9-2009-0002
NPDES NO. CAS0108740**

December 16, 2009

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN DIEGO REGION**

9174 Sky Park Court, Suite 100, San Diego, California 92123-4340

Phone • (858) 467-2952 • Fax (858) 571-6972

<http://www.waterboards.ca.gov/sandiego>

To request copies of the Orange County Municipal Storm Water Permit, please contact Ben Neill, Water Resources Control Engineer at (858) 467 – 2983, bneill@waterboards.ca.gov

Documents also are available at: <http://www.waterboards.ca.gov/sandiego>

**WASTE DISCHARGE REQUIREMENTS FOR
DISCHARGES OF RUNOFF FROM THE
MUNICIPAL SEPARATE STORM SEWER SYSTEMS (MS4s)
DRAINING THE WATERSHED OF
THE COUNTY OF ORANGE, THE INCORPORATED CITIES OF
ORANGE COUNTY, AND THE ORANGE COUNTY FLOOD
CONTROL DISTRICT WITHIN THE SAN DIEGO REGION**

Adopted by the
California Regional Water Quality Control Board
San Diego Region
on December 16, 2009

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN DIEGO REGION**

**9174 Sky Park Court, Suite 100
San Diego, California 92123-4340**

Telephone (858) 467-2952

STATE OF CALIFORNIA
ARNOLD SCHWARZENEGGER, Governor
LINDA S. ADAMS, Agency Secretary, California Environmental Protection Agency



**California Regional Water Quality Control Board
San Diego Region**

David King <i>Vice Chair</i>	Recreation / Wildlife
Eric Anderson	Irrigated Agriculture
Wayne Rayfield	Water Quality
Grant Destache	Industrial Water Use
George Loveland	Water Supply
Marc Luker	Undesignated (Public)

David W. Gibson, *Executive Officer*
Michael P. McCann, *Assistant Executive Officer*

This permit was prepared under the direction of

David T. Barker P.E., *Chief, Water Resource Protection Branch*

by

Jimmy G. Smith, *Senior Environmental Scientist*
Ben Neill, *Water Resource Control Engineer*
Chad Loflen, *Environmental Scientist*

Table of Contents

FINDINGS:

A. BASIS FOR THE ORDER.....	1
B. REGULATED PARTIES.....	1
C. DISCHARGE CHARACTERISTICS.....	2
D. RUNOFF MANAGEMENT PROGRAMS.....	6
E. STATUTE AND REGULATORY CONSIDERATIONS.....	12
F. PUBLIC PROCESS.....	17

DISCHARGE and LEGAL PROVISIONS:

A. PROHIBITIONS AND RECEIVING WATER LIMITATIONS.....	18
B. NON-STORM WATER DISCHARGES.....	19
C. NON-STORM WATER ACTION LEVELS.....	21
D. STORM WATER ACTION LEVELS.....	25
E. LEGAL AUTHORITY.....	26

PROGRAM PROVISIONS:

F. JURISDICTIONAL RUNOFF MANAGEMENT PROGRAM (JRMP).....	28
1.DEVELOPMENT PLANNING COMPONENT.....	28
2.CONSTRUCTION COMPONENT.....	48
3.EXISTING DEVELOPMENT COMPONENT.....	54
4.ILLICIT DISCHARGE DETECTION AND ELIMINATION.....	69
5.PUBLIC PARTICIPATION COMPONENT.....	72
G. WATERSHED RUNOFF MANAGEMENT PROGRAM.....	73
H. FISCAL ANALYSIS.....	77
I. TOTAL MAXIMUM DAILY LOADS.....	78

REPORTING and PROGRAM MANAGEMENT PROVISIONS

J. PROGRAM EFFECTIVENESS ASSESSMENT AND REPORTING.....	79
K. REPORTING.....	83
L. MODIFICATION OF PROGRAMS.....	90
M. PRINCIPAL COPERMITTEE RESPONSIBILITIES.....	90
N. RECEIVING WATERS AND MS4 DISCHARGE MONITORING AND REPORTING PROGRAM.....	90
O. STANDARD PROVISIONS, REPORTING REQUIREMENTS, AND NOTIFICATIONS.....	91

Attachment A – Basin Plan Prohibitions

Attachment B – Standard Provisions, Reporting Requirements, and Notifications

Attachment C – Definitions

Attachment D – Scheduled Submittal Summary and Reporting Checklist Requirements

Attachment E – Receiving Waters And MS4 Discharge Monitoring And Reporting
Program No. R9-2009-0002

Attachment F – Data

The California Regional Water Quality Control Board, San Diego Region (hereinafter Regional Board), finds that:

A. BASIS FOR THE ORDER

1. This Order is based on the federal Clean Water Act (CWA), the Porter-Cologne Water Quality Control Act (Division 7 of the Water Code, commencing with Section 13000), applicable State and federal regulations, all applicable provisions of statewide Water Quality Control Plans and Policies adopted by the State Water Resources Control Board (State Board), the Water Quality Control Plan for the San Diego Basin adopted by the Regional Board, the California Toxics Rule, and the California Toxics Rule Implementation Plan.
2. This Order reissues National Pollutant Discharge Elimination System (NPDES) Permit No. CAS0108740, which was first adopted by the Regional Board on July 16, 1990 (Order No. 90-38), and then reissued on August 8, 1996 (Order No. 96-03) and February 13, 2002 (Order No. R9-2002-01). On August 21, 2006, in accordance with Order No. R9-2002-01, the County of Orange, as the Principal Copermittee, submitted a Report of Waste Discharge (ROWD) for reissuance of the municipal separate storm sewer system (MS4) Permit.
3. This Order is consistent with the following precedential Orders adopted by the State Water Resources Control Board (State Board) addressing MS4 NPDES Permits: Order 99-05, Order WQ-2000-11, Order WQ 2001-15, Order WQO 2002-0014, and Order WQ-2009-0008 (*SWRCB/OCC FILE A-1780*).
4. The Fact Sheet / Technical Report for the Order No. R9-2009-0002, NPDES No. CAS0108740, Waste Discharge Requirements for Discharges of Runoff from the Municipal Separate Storm Sewer Systems (MS4s) Draining the Watersheds of the County of Orange, the Incorporated Cities of Orange County, and the Orange County Flood Control District Within the San Diego Region includes cited regulatory and legal references and additional explanatory information and data in support of the requirements of this Permit. This information, including any supplements thereto, and any response to comments on the Tentative Orders, is hereby incorporated by reference into these findings.

B. REGULATED PARTIES

1. Each of the persons in Table 1 below, hereinafter called Copermittees or dischargers, owns or operates an MS4, through which it discharges runoff into waters of the United States within the San Diego Region. These MS4s fall into one or more of the following categories: (1) a medium or large MS4 that services a population of greater than 100,000 or 250,000 respectively; or (2) a small MS4 that is "interrelated" to a medium or large MS4; or (3) an MS4 which contributes to a

violation of a water quality standard; or (4) an MS4 which is a significant contributor of pollutants to waters of the United States (waters of the U.S).

Table 1. Municipal Copermittees

1. City of Aliso Viejo	8. City of Mission Viejo
2. City of Dana Point	9. City of Rancho Santa Margarita
3. City of Laguna Beach	10. City of San Clemente
4. City of Laguna Hills	11. City of San Juan Capistrano
5. City of Laguna Niguel	12. County of Orange
6. City of Laguna Woods	13. Orange County Flood Control District
7. City of Lake Forest	

C. DISCHARGE CHARACTERISTICS

1. Runoff discharged from an MS4 contains waste, as defined in the California Water Code (CWC), and pollutants that adversely affect the quality of the waters of the State. The discharge of runoff from an MS4 is a "discharge of pollutants from a point source" into waters of the U.S. as defined in the CWA.
2. MS4 storm water and non-storm water discharges are likely to contain pollutants that cause or threaten to cause a violation of water quality standards, as outlined in the Regional Board's Water Quality Control Plan for the San Diego Basin (Basin Plan). Storm water and non-storm water discharges from the MS4 are subject to the conditions and requirements established in the San Diego Basin Plan for point source discharges. These surface water quality standards must be complied with at all times, irrespective of the source and manner of discharge.
3. The most common categories of pollutants in runoff include total suspended solids, sediment, pathogens (e.g., bacteria, viruses, protozoa); heavy metals (e.g., copper, lead, zinc and cadmium); petroleum products and polynuclear aromatic hydrocarbons; synthetic organics (e.g., pesticides, herbicides, and PCBs); nutrients (e.g., nitrogen and phosphorus fertilizers); oxygen-demanding substances (decaying vegetation, animal waste); detergents; and trash.
4. The discharge of pollutants and/or increased flows from MS4s may cause or threaten to cause the concentration of pollutants to exceed applicable receiving water quality objectives and/or impair or threaten to impair designated beneficial uses resulting in a condition of pollution (i.e., unreasonable impairment of water quality for designated beneficial uses), contamination, or nuisance.
5. Pollutants in runoff can threaten and adversely affect human health. Human illnesses have been clearly linked to recreating near storm drains flowing to coastal waters. Also, runoff pollutants in receiving waters can bioaccumulate in the tissues of invertebrates and fish, which may be eventually consumed by humans.

6. Runoff discharges from MS4s often contain pollutants that cause toxicity to aquatic organisms (i.e., adverse responses of organisms to chemicals or physical agents ranging from mortality to physiological responses such as impaired reproduction or growth anomalies). Toxic pollutants impact the overall quality of aquatic systems and beneficial uses of receiving waters.
7. The Copermitttees discharge runoff into lakes, drinking water reservoirs, rivers, streams, creeks, bays, estuaries, coastal lagoons, the Pacific Ocean, and tributaries thereto within one of the eleven hydrologic units (San Juan Hydrologic Unit) comprising the San Diego Region as shown in Tables 2a and 2b. Some of the receiving water bodies have been designated as impaired by the Regional Board and the United States Environmental Protection Agency (USEPA) in 2006 pursuant to CWA section 303(d). Also shown in the Tables are the watershed management areas (WMAs) as defined in the Regional Board report, Watershed Management Approach, January 2002.

Table 2a. Common Watersheds and CWA Section 303(d) Impaired Waters

Regional Board Watershed Management Area (WMA)	Hydrologic Area (HA) or Hydrologic Subarea (HSA) of the San Juan Hydrologic Unit	Major Receiving Water Bodies	303(d) Pollutant(s)/stressor or Water Quality Effect ¹
Laguna Coastal Streams	Laguna HA, excluding Aliso HSA and Dana Point HSA	Laguna Canyon Creek, Pacific Ocean	Bacterial indicators Sediment toxicity
Aliso Creek	Aliso HSA	Aliso Creek, English Canyon, Pacific Ocean	Toxicity Phosphorus Bacterial indicators Benzo[b]fluoranthene Dieldrin Sediment Toxicity
Dana Point Coastal Streams	Dana Point HSA	Dana Point Harbor, Salt Creek, Pacific Ocean	Bacterial indicators
San Juan Creek	Mission Viejo HA	San Juan Creek, Trabuco Creek, Oso Creek, Canada Gobernadora, Bell Canyon, Verdugo Canyon, Pacific Ocean	Bacterial indicators DDE Chloride Sulfates Total dissolved solids

¹ The listed 303(d) pollutant(s) do not necessarily reflect impairment of the entire corresponding WMA or all corresponding major surface water bodies. The specific impaired portions of each WMA are listed in the State Water Resources Control Board's 2006 Section 303(d) List of Water Quality Limited Segments.

Table 2a. Common Watersheds and CWA Section 303(d) Impaired Waters

Regional Board Watershed Management Area (WMA)	Hydrologic Area (HA) or Hydrologic Subarea (HSA) of the San Juan Hydrologic Unit	Major Receiving Water Bodies	303(d) Pollutant(s)/stressor or Water Quality Effect ¹
San Clemente Coastal Streams	San Clemente HA	Prima Deshecha, Segunda Deshecha, Pacific Ocean	Bacterial indicators Phosphorus Turbidity
San Mateo Creek	San Mateo HA	San Mateo Creek, Christianitos Creek, Pacific Ocean	

Table 2b. Common Watersheds and Municipalities

Municipality	Laguna Coastal Streams	Aliso Creek	Dana Point Coastal Streams	San Juan Creek	San Clemente Coastal Streams	San Mateo Creek
Aliso Viejo	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>				
Dana Point			<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
Laguna Beach	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>				
Laguna Hills *		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		
Laguna Niguel		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
Laguna Woods *		<input checked="" type="checkbox"/>				
Lake Forest *		<input checked="" type="checkbox"/>				
Mission Viejo		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		
Rancho Santa Margarita				<input checked="" type="checkbox"/>		
San Clemente					<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
San Juan Capistrano				<input checked="" type="checkbox"/>		
County of Orange *	<input checked="" type="checkbox"/>					
Orange County Flood Control District *	<input checked="" type="checkbox"/>					

* Municipality also includes areas within watersheds of the Santa Ana Regional Board that are outside the scope of this Order

8. Trash is a persistent pollutant which can enter receiving waters from the MS4 resulting in accumulation and transport in receiving waters over time. Trash poses a serious threat to the Beneficial Uses of the receiving waters, including, but not limited to, human health, rare and endangered species, navigation and human recreation.
9. The Copermittees' water quality monitoring data submitted to date documents persistent violations of Basin Plan water quality objectives for various runoff-related pollutants (fecal coliform bacteria, total suspended solids, turbidity, metals; etc.) at

various watershed monitoring stations. Persistent toxicity has also been observed at some watershed monitoring stations. In addition, bioassessment data indicates that the majority of urbanized receiving waters have Poor to Very Poor Index of Biotic Integrity ratings. In sum, the above findings indicate that runoff discharges are causing or contributing to water quality impairments, and are a leading cause of such impairments in Orange County.

10. When natural vegetated pervious ground cover is converted to impervious surfaces such as paved highways, streets, rooftops, and parking lots, the natural absorption and infiltration abilities of the land are lost. Therefore, runoff leaving a developed area is significantly greater in runoff volume, velocity, and peak flow rate than pre-development runoff from the same area. Runoff durations can also increase as a result of flood control and other efforts to control peak flow rates. Increased volume, velocity, rate, and duration of runoff, and decreased natural clean sediment loads, greatly accelerate the erosion of downstream natural channels. Significant declines in the biological integrity and physical habitat of streams and other receiving waters have been found to occur with as little as a 3-5 percent conversion from natural to impervious surfaces. The increased runoff characteristics from new development must be controlled to protect against increased erosion of channel beds and banks, sediment pollutant generation, or other impacts to beneficial uses and stream habitat due to increased erosive force.
11. Development creates new pollution sources as human population density increases and brings with it proportionately higher levels of car emissions, car maintenance wastes, municipal sewage, pesticides, household hazardous wastes, pet wastes, trash, etc. which can either be washed or directly dumped into the MS4. As a result, the runoff leaving the developed urban area is significantly greater in pollutant load than the pre-development runoff from the same area. These increased pollutant loads must be controlled to protect downstream receiving water quality.
12. Development and urbanization especially threaten environmentally sensitive areas (ESAs), such as water bodies designated as supporting a RARE beneficial use (supporting rare, threatened or endangered species) and CWA 303(d)-impaired water bodies. Such areas have a much lower capacity to withstand pollutant shocks than might be acceptable in other areas. In essence, development that is ordinarily insignificant in its impact on the environment may become significant in a particularly sensitive environment. Therefore, additional control to reduce storm water pollutants from new and existing development may be necessary for areas adjacent to or discharging directly to an ESA.
13. Although dependent on several factors, the risks typically associated with properly managed infiltration of runoff (especially from residential land use areas) are not significant. The risks associated with infiltration can be managed by many techniques, including (1) designing landscape drainage features that promote infiltration of runoff, but do not "inject" runoff (injection bypasses the natural processes of filtering and transformation that occur in the soil); (2) taking reasonable

steps to prevent the illegal disposal of wastes; (3) protecting footings and foundations; (4) ensuring that each drainage feature is adequately maintained in perpetuity; and (5) pretreatment.

14. Non-storm water (dry weather) discharge from the MS4 is not considered a storm water (wet weather) discharge and therefore is not subject to regulation under the Maximum Extent Practicable (MEP) standard from CWA 402(p)(3)(B)(iii), which is explicitly for "Municipal ... *Stormwater Discharges* (emphasis added)" from the MS4. Non-storm water discharges, per CWA 402(p)(3)(B)(ii), are to be effectively prohibited. Such dry weather non-storm water discharges have been shown to contribute significant levels of pollutants and flow in arid, developed Southern California watersheds and are to be effectively prohibited under the Clean Water Act.
15. Non-storm water discharges to the MS4 granted an influent exception [i.e., which are exempt from the effective prohibition requirement set forth in CWA section 402(p)(3)(B)(ii)] under 40 CFR 122. 26 are included within this Order. Any exempted discharges identified by Copermittees as a source of pollutants are subsequently required to be *addressed* (emphasis added) as illicit discharges through prohibition and incorporation into existing IC/ID programs. The Copermittees have identified landscape irrigation, irrigation water and lawn water, previously exempted discharges, as a source of pollutants and conveyance of pollutants to waters of the United States.

D. RUNOFF MANAGEMENT PROGRAMS

1. General

- a. This Order specifies requirements necessary for the Copermittees to reduce the discharge of pollutants in storm water runoff to the maximum extent practicable (MEP). However, since MEP is a dynamic performance standard, which evolves over time as runoff management knowledge increases, the Copermittees' runoff management programs must continually be assessed and modified to incorporate improved programs, control measures, best management practices (BMPs), etc. in order to achieve the evolving MEP standard. Absent evidence to the contrary, this continual assessment, revision, and improvement of runoff management program implementation is expected to ultimately achieve compliance with water quality standards in the Region.
- b. The Copermittees have generally been implementing the jurisdictional runoff management programs required pursuant to Order No. 2002-01 since February 13, 2003. Prior to that, the Copermittees were regulated by Order No. 96-03 since August 8, 1996. Runoff discharges, however, continue to cause or contribute to violations of water quality standards as evidenced by the Copermittees monitoring results.

- c. This Order contains new or modified requirements that are necessary to improve Copermittees' efforts to reduce the discharge of pollutants in storm water runoff to the MEP and achieve water quality standards. Some of the new or modified requirements, such as the revised Watershed Runoff Management Program section, are designed to specifically address high priority water quality problems. Other new or modified requirements address program deficiencies that have been noted during audits, report reviews, and other Regional Board compliance assessment activities.
- d. Updated Jurisdictional Runoff Management Plans (JRMPs) and Watershed Runoff Management Plans (WRMPs), which describe the Copermittees' runoff management programs in their entirety, are needed to guide the Copermittees' runoff management efforts and aid the Copermittees in tracking runoff management program implementation. It is practicable for the Copermittees to update the JRMPs and WRMPs within one year, since significant efforts to develop these programs have already occurred.
- e. Pollutants can be effectively reduced in storm water runoff by the application of a combination of pollution prevention, source control, and treatment control BMPs. Pollution prevention is the reduction or elimination of pollutant generation at its source and is the best "first-line of defense." Source control BMPs (both structural and non-structural) minimize the contact between pollutants and flows (e.g., rerouting run-on around pollutant sources or keeping pollutants on-site and out of receiving waters). Treatment control BMPs remove pollutants that have been mobilized by wet-weather or dry-weather flows.
- f. Runoff needs to be addressed during the three major phases of urban development (planning, construction, and use) in order to reduce the discharge of pollutants from storm water to the MEP, effectively prohibit non-storm water discharges and protect receiving waters. Development which is not guided by water quality planning policies and principles can unnecessarily result in increased pollutant load discharges, flow rates, and flow durations which can negatively impact receiving water beneficial uses. Construction sites without adequate BMP implementation result in sediment runoff rates which greatly exceed natural erosion rates of undisturbed lands, causing siltation and impairment of receiving waters. Existing development generates substantial pollutant loads which are discharged in runoff to receiving waters.
- g. Annual reporting requirements included in this Order are necessary to meet federal requirements and to evaluate the effectiveness and compliance of the Copermittees' programs.
- h. This Order establishes Storm Water Action Levels (SALs) for selected pollutants based on USEPA Rain Zone 6 (arid southwest) Phase I MS4 monitoring data for pollutants in storm water. The SALs were computed as the 90th percentile of the data set, utilizing the statistical based population approach, one of three

approaches recommended by the California Water Board's Storm Water Panel in its report, 'The Feasibility of Numerical Effluent Limits Applicable to Discharges of Storm Water Associated with Municipal, Industrial and Construction Activities (June 2006). SALs are identified in Section D of this Order. Copermittees shall implement a timely, comprehensive, cost-effective storm water pollution control program to reduce the discharge of pollutants in storm water from the permitted areas so as not to exceed the SALs. Exceedance of SALs may indicate inadequacy of programmatic measures and BMPs required in this Order.

2. Development Planning

- a. The Standard Storm Water Mitigation Plan (SSMP) requirements contained in this Order are consistent with Order WQ-2000-11 adopted by the State Water Resources Control Board (State Board) on October 5, 2000. In the precedential order, the State Board found that the design standards, which essentially require that runoff generated by 85 percent of storm events from specific development categories be infiltrated or treated, reflect the MEP standard. The order also found that the SSMP requirements are appropriately applied to the majority of the Priority Development Project categories contained in Section D.1 of this Order. The State Board also gave Regional Water Quality Control Boards the needed discretion to include additional categories and locations, such as retail gasoline outlets (RGOs), in SSMPs.
- b. Controlling runoff pollution by using a combination of onsite source control and site design BMPs augmented with treatment control BMPs before the runoff enters the MS4 is important for the following reasons: (1) Many end-of-pipe BMPs (such as diversion to the sanitary sewer) are typically ineffective during significant storm events. Whereas, onsite source control BMPs can be applied during all runoff conditions; (2) End-of-pipe BMPs are often incapable of capturing and treating the wide range of pollutants which can be generated on a sub-watershed scale; (3) End-of-pipe BMPs are more effective when used as polishing BMPs, rather than the sole BMP to be implemented; (4) End-of-pipe BMPs do not protect the quality or beneficial uses of receiving waters between the pollutant source and the BMP; and (5) Offsite end-of-pipe BMPs do not aid in the effort to educate the public regarding sources of pollution and their prevention.
- c. Use of Low-Impact Development (LID) site design BMPs at new development, redevelopment and retrofit projects can be an effective means for minimizing the impact of storm water runoff discharges from the development projects on receiving waters. LID is a site design strategy with a goal of maintaining or replicating the pre-development hydrologic regime through the use of design techniques. LID site design BMPs help preserve and restore the natural hydrologic cycle of the site, allowing for filtration and infiltration which can greatly reduce the volume, peak flow rate, velocity, and pollutant loads of storm water runoff. Current runoff management, knowledge, practices and technology have

resulted in the use of LID BMPs as an acceptable means of meeting the storm water MEP standard.

- d. Retail Gasoline Outlets (RGOs) are significant sources of pollutants in storm water runoff. RGOs are points of convergence for motor vehicles for automotive related services such as repair, refueling, tire inflation, and radiator fill-up and consequently produce significantly higher loadings of hydrocarbons and trace metals (including copper and zinc) than other developed areas.
- e. Industrial sites are significant sources of pollutants in runoff. Pollutant concentrations and loads in runoff from industrial sites are similar or exceed pollutant concentrations and loads in runoff from other land uses, such as commercial or residential land uses. As with other land uses, LID site design, source control, and treatment control BMPs are needed at industrial sites in order to meet the MEP standard. These BMPs are necessary where the industrial site is larger than 10,000 square feet. The 10,000 square feet threshold is appropriate, since it is consistent with requirements in other Phase I NPDES storm water regulations throughout California.
- f. If not properly designed or maintained, certain BMPs implemented or required by municipalities for runoff management may create a habitat for vectors (e.g. mosquitoes and rodents). Proper BMP design and maintenance to avoid standing water, however, can prevent the creation of vector habitat. Nuisances and public health impacts resulting from vector breeding can be prevented with close collaboration and cooperative effort between municipalities, the Orange County Vector Control District, and the California Department of Public Health during the development and implementation of runoff management programs.
- g. The increased volume, velocity, frequency and discharge duration of storm water runoff from developed areas has the potential to greatly accelerate downstream erosion, impair stream habitat in natural drainages, and negatively impact beneficial uses. Development and urbanization increase pollutant loads in storm water runoff and the volume of storm water runoff. Impervious surfaces can neither absorb water nor remove pollutants and thus lose the purification and infiltration provided by natural vegetated soil. Hydromodification measures for discharges to hardened channels are needed for the future restoration of the hardened channels to their natural state, thereby restoring the chemical, physical, and biological integrity and Beneficial Uses of local receiving waters.

3. Construction and Existing Development

- a. In accordance with federal NPDES regulations and to ensure the most effective oversight of industrial and construction site discharges, discharges of runoff from industrial and construction sites are subject to dual (State and local) storm water regulation. Under this dual system, each Copermitttee is responsible for enforcing its local permits, plans, and ordinances, and the Regional Board is

responsible for enforcing the General Construction Activities Storm Water Permit, State Board Order 99-08 DWQ, NPDES No. CAS000002 (General Construction Permit) and the General Industrial Activities Storm Water Permit, State Board Order 97-03 DWQ, NPDES No. CAS000001 (General Industrial Permit) and any reissuance of these permits. NPDES municipal regulations require that municipalities develop and implement measures to address runoff from industrial and construction activities. Those measures may require the implementation of additional BMPs than are required under the statewide general permits for activities subject to both State and local regulation.

- b. Identification of sources of pollutants in runoff (such as municipal areas and activities, industrial and commercial sites/sources, construction sites, and residential areas), development and implementation of BMPs to address those sources, and updating ordinances and approval processes are necessary for the Copermitees to ensure that discharges of pollutants from its MS4 in storm water are reduced to the MEP and that non-storm water discharges are not occurring. Inspections and other compliance verification methods are needed to ensure minimum BMPs are implemented. Inspections are especially important at high risk areas for pollutant discharges.
- c. Historic and current development makes use of natural drainage patterns and features as conveyances for runoff. Urban streams used in this manner are part of the municipalities MS4 regardless of whether they are natural, anthropogenic, or partially modified features. In these cases, the urban stream is both an MS4 and receiving water.
- d. As operators of the MS4s, the Copermitees cannot passively receive and discharge pollutants from third parties. By providing free and open access to an MS4 that conveys discharges to waters of the U.S., the operator essentially accepts responsibility for discharges into the MS4 that it does not prohibit or control. These discharges may cause or contribute to a condition of contamination or a violation of water quality standards.
- e. Waste and pollutants which are deposited and accumulate in MS4 drainage structures will be discharged from these structures to waters of the U.S. unless they are removed. These discharges may cause or contribute to, or threaten to cause or contribute to, a condition of pollution in receiving waters. For this reason, pollutant discharges from storm water into MS4s must be reduced using a combination of management measures, including source control, and an effective MS4 maintenance program must be implemented by each Copermitee.
- f. Enforcement of local runoff related ordinances, permits, and plans is an essential component of every runoff management program and is specifically required in the federal storm water regulations and this Order. Each Copermitee is individually responsible for adoption and enforcement of ordinances and/or policies, implementation of identified control measures/BMPs needed to prevent

or reduce pollutants in storm water runoff, and for the allocation of funds for the capital, operation and maintenance, administrative, and enforcement expenditures necessary to implement and enforce such control measures/BMPs under its jurisdiction. Education is an important aspect of every effective runoff management program and the basis for changes in behavior at a societal level. Education of municipal planning, inspection, and maintenance department staffs is especially critical to ensure that in-house staffs understand how their activities impact water quality, how to accomplish their jobs while protecting water quality, and their specific roles and responsibilities for compliance with this Order. Public education, designed to target various urban land users and other audiences, is also essential to inform the public of how individual actions affect receiving water quality and how adverse effects can be minimized.

- g. Public participation during the development of runoff management programs is necessary to ensure that all stakeholder interests and a variety of creative solutions are considered.
- h. Retrofitting existing development with storm water treatment controls, including LID, is necessary to address storm water discharges from existing development that may cause or contribute to a condition of pollution or a violation of water quality standards. Although SSMP-BMPs are required for redevelopment, the current rate of redevelopment will not address water quality problems in a timely manner. Cooperation with private landowners is necessary to effectively identify, implement and maintain retrofit projects for the preservation, restoration, and enhancement of water quality.

4. Watershed Runoff Management

- a. Since runoff within a watershed can flow from and through multiple land uses and political jurisdictions, watershed-based runoff management can greatly enhance the protection of receiving waters. Such management provides a means to focus on the most important water quality problems in each watershed. By focusing on the most important water quality problems, watershed efforts can maximize protection of beneficial use in an efficient manner. Effective watershed-based runoff management actively reduces pollutant discharges and abates pollutant sources causing or contributing to watershed water quality problems. Watershed-based runoff management that does not actively reduce pollutant discharges and abate pollutant sources causing or contributing to watershed water quality problems can necessitate implementation of the iterative process outlined in section A.3 of the Tentative Order. Watershed management of runoff does not require Copermittees to expend resources outside of their jurisdictions. Watershed management requires the Copermittees within a watershed to develop a watershed-based management strategy, which can then be implemented on a jurisdictional basis.

- b. Some runoff issues, such as general education and training, can be effectively addressed on a regional basis. Regional approaches to runoff management can improve program consistency and promote sharing of resources, which can result in implementation of more efficient programs.
- c. It is important for the Copermittees to coordinate their water quality protection and land use planning activities to achieve the greatest protection of receiving water bodies. Copermittee coordination with other watershed stakeholders, especially the State of California Department of Transportation, the United States Department of Defense, and water and sewer districts, is also important.

E. STATUTE AND REGULATORY CONSIDERATIONS

1. The Receiving Water Limitations (RWL) language specified in this Order is consistent with language recommended by the USEPA and established in State Board Water Quality Order 99-05, *Own Motion Review of the Petition of Environmental Health Coalition to Review Waste Discharge Requirements Order No. 96-03, NPDES Permit No. CAS0108740*, adopted by the State Board on June 17, 1999. The RWL in this Order require compliance with water quality standards, which for storm water discharges is to be achieved through an iterative approach requiring the implementation of improved and better-tailored BMPs over time. Compliance with receiving water limits based on applicable water quality standards is necessary to ensure that MS4 discharges will not cause or contribute to violations of water quality standards and the creation of conditions of pollution.
2. The Water Quality Control Plan for the San Diego Basin (Basin Plan), identifies the following beneficial uses for surface waters in Orange County: Municipal and Domestic Supply (MUN)², Agricultural Supply (AGR), Industrial Process Supply (PROC), Industrial Service Supply (IND), Ground Water Recharge (GWR), Contact Water Recreation (REC1), Non-contact Water Recreation (REC2), Warm Freshwater Habitat (WARM), Cold Freshwater Habitat (COLD), Wildlife Habitat (WILD), Rare, Threatened, or Endangered Species (RARE), Freshwater Replenishment (FRSH), Hydropower Generation (POW), and Preservation of Biological Habitats of Special Significance (BIOL). The following additional beneficial uses are identified for coastal waters of Orange County: Navigation (NAV), Commercial and Sport Fishing (COMM), Estuarine Habitat (EST), Marine Habitat (MAR), Aquaculture (AQUA), Migration of Aquatic Organisms (MIGR), Spawning, Reproduction, and/or Early Development (SPWN), and Shellfish Harvesting (SHELL).
3. This Order is in conformance with State Board Resolution No. 68-16, *Statement of Policy with Respect to Maintaining High Quality Waters in California*, and the federal Antidegradation Policy described in 40 CFR 131.12.

² Subject to exceptions under the "Sources of Drinking Waters" Policy (Resolution No. 89-33)

4. Section 6217(g) of the Coastal Zone Act Reauthorization Amendments of 1990 (CZARA) requires coastal states with approved coastal zone management programs to address non-point pollution impacting or threatening coastal water quality. CZARA addresses five sources of non-point pollution: agriculture, silviculture, urban, marinas, and hydromodification. This NPDES permit addresses the management measures required for the urban category, with the exception of septic systems. The adoption and implementation of this NPDES permit relieves the Copermittee from developing a non-point source plan, for the urban category, under CZARA. The Regional Board addresses septic systems through the administration of other programs.
5. Section 303(d)(1)(A) of the CWA requires that "Each state must identify those waters within its boundaries for which the effluent limitations... are not stringent enough to implement any water quality standard (WQS) applicable to such waters." The CWA also requires states to establish a priority ranking of impaired water bodies known as Water Quality Limited Segments and to establish Total Maximum Daily Loads (TMDLs) for such waters. This priority list of impaired water bodies is called the Section 303(d) List. The current Section 303(d) List was approved by the State Board on October 25, 2006. On June 28, 2007 the 2006 303(d) list for California was given final approval by the United States Environmental Protection Agency (USEPA).
6. This Order does not constitute an unfunded local government mandate subject to subvention under Article XIII B, Section (6) of the California Constitution for several reasons, including, but not limited to, the following. First, this Order implements federally mandated requirements under federal Clean Water Act section 402. (33 U.S.C. § 1342(p)(3)(B).) Second, the local agency Copermittees' obligations under this Order are similar to, and in many respects less stringent than, the obligations of non-governmental and new dischargers who are issued NPDES permits for storm water and non-storm water discharges. Third, the local agency Copermittees have the authority to levy service charges, fees, or assessments sufficient to pay for compliance with this Order. Fourth, the Copermittees have requested permit coverage in lieu of compliance with the complete prohibition against the discharge of pollutants contained in federal Clean Water Act section 301, subdivision (a) (33 U.S.C. § 1311(a)) and in lieu of numeric restrictions on their storm water discharges. Fifth, the local agencies' responsibility for preventing discharges of waste that can create conditions of pollution or nuisance from conveyances that are within their ownership or control under State law predates the enactment of Article XIII B, Section (6) of the California Constitution. Likewise, the provisions of this Order to implement total maximum daily loads (TMDLs) are federal mandates. The federal Clean Water Act requires TMDLs to be developed for water bodies that do not meet federal water quality standards. (33 U.S.C. sec. 1313(d).) Once the U.S. Environmental Protection Agency or a state develops a TMDL, federal law requires that permits must contain effluent limitations consistent with the assumptions of any applicable wasteload allocation. (40 C.F.R. sec. 122.44(d)(1)(vii)(B).)

7. Runoff treatment and/or mitigation must occur prior to the discharge of runoff into receiving waters. Treatment BMPs must not be constructed in waters of the U.S. or State unless the runoff flows are sufficiently pretreated to protect the values and functions of the water body. Federal regulations at 40 CFR 131.10(a) state that in no case shall a state adopt waste transport or waste assimilation as a designated use for any waters of the U.S. Authorizing the construction of an runoff treatment facility within a water of the U.S., or using the water body itself as a treatment system or for conveyance to a treatment system, would be tantamount to accepting waste assimilation as an appropriate use for that water body. Furthermore, the construction, operation, and maintenance of a pollution control facility in a water body can negatively impact the physical, chemical, and biological integrity, as well as the beneficial uses, of the water body. Without federal authorization (e.g., pursuant to Clean Water Act Section 404), waters of the U.S. may not be converted into, or used as, waste treatment or conveyance facilities. Similarly, waste discharge requirements pursuant to California Water Code Section 13260 are required for the conversion or use of waters of the State as waste treatment or conveyance facilities. Diversion from waters of the U.S./State to treatment facilities and subsequent return to waters of the U.S. is allowable, provided that the effluent complies with applicable NPDES requirements.
8. The issuance of waste discharge requirements and an NPDES permit for the discharge of runoff from MS4s to waters of the U.S. is exempt from the requirement for preparation of environmental documents under the California Environmental Quality Act (CEQA) (Public Resources Code, Division 13, Chapter 3, section 21000 et seq.) in accordance with the CWC section 13389.
9. Multiple water bodies in Orange County have been identified as impaired and placed on the 303(d) list. In 2004, Bacteria Impaired Waters TMDL Project II included six bacteria impaired shorelines in Dana Point Harbor and San Diego Bay: Baby Beach in Dana Point Harbor and Shelter Island Shoreline Park, B Street, G Street Pier, Tideland Park, and Chula Vista Marina in San Diego Bay. Since then, only Baby Beach in Dana Point Harbor and Shelter Island Shoreline Park in San Diego Bay can be confirmed as still impaired by indicator bacteria. On June 11, 2008 the Regional Board adopted a Basin Plan amendment to incorporate *Bacteria Impaired Waters TMDL Project II for San Diego Bay and Dana Point Harbor Shorelines*. On June 16, 2009, the State Board approved the Basin Plan amendment. This action meets requirements of section 303(d) of the Clean Water Act (CWA). The Basin Plan amendment process is authorized under section 13240 of the Water Code. The State's Office of Administrative Law (OAL) approved the TMDLs on September 15, 2009. The effective date of the TMDLs is the date of OAL approval. USEPA approved the TMDLs on October 26, 2009.
10. Storm water discharges from developed and developing areas in Orange County are significant sources of certain pollutants that cause, may be causing, threatening to cause or contributing to water quality impairment in the waters of Orange County.

Furthermore, as delineated in the CWA section 303(d) list in Table 3, the Regional Board has found that there is a reasonable potential that municipal storm water and non-storm water discharges from MS4s cause or may cause or contribute to an excursion above water quality standards for the following pollutants: Indicator Bacteria, Phosphorous, Toxicity and Turbidity. In accordance with CWA section 303(d), the Regional Board is required to establish Total Maximum Daily Loads (TMDLs) for these pollutants to these waters to eliminate impairment and attain water quality standards. Therefore, certain early pollutant control actions and further pollutant impact assessments by the Copermitees are warranted and required pursuant to this Order.

Table 3. 2006 Section 303(d) Listed Waterbodies in So. Orange County

Waterbody	Pollutant
Aliso Creek	Indicator Bacteria, Phosphorus, Toxicity
Aliso Creek Mouth	Indicator Bacteria
Dana Point Harbor	Indicator Bacteria
English Canyon Creek	Benzo[b]fluoranthene, Dieldrin, Sediment Toxicity
Laguna Canyon Channel	Sediment Toxicity
Oso Creek (at Mission Viejo Golf Course)	Chloride, Sulfates, Total Dissolved Solids
Pacific Ocean Shoreline, Aliso HSA	Indicator Bacteria
Pacific Ocean Shoreline, Dana Point HSA	Indicator Bacteria
Pacific Ocean Shoreline, Laguna Beach HSA	Indicator Bacteria
Pacific Ocean Shoreline, Lower San Juan HSA	Indicator Bacteria
Pacific Ocean Shoreline, San Clemente HA	Indicator Bacteria
Pacific Ocean Shoreline, San Joaquin Hills HSA	Indicator Bacteria
Prima Deshecha Creek	Phosphorus, Turbidity
San Juan Creek	DDE, Indicator Bacteria
San Juan Creek (mouth)	Indicator Bacteria
Segunda Deshecha Creek	Phosphorus, Turbidity

11. This Order incorporates only those MS4 Waste Load Allocations (WLAs) developed in TMDLs that have been adopted by the Regional Water Board and have been approved by the State Board, Office of Administrative Law and U.S. EPA. Approved TMDL WLAs are to be addressed using water quality-based effluent limitations (WQBELs) calculated as numeric limitations (either in the receiving waters and/or at the point of MS4 discharge) and/or as BMPs. In most cases, the numeric limitation must be achieved to ensure the adequacy of the BMP program. Waste load

allocations for storm water and non-storm water discharges have been included within this Order only if the TMDL has received all necessary approvals. This Order establishes WQBELs and conditions consistent with the requirements and assumptions of the WLAs in the TMDLs as required by 40 CFR 122.44(d)(1)(vii)(B).

A TMDL is the total amount of a particular pollutant that a water body can receive and still meet Water Quality Standards (WQSs), which are comprised of Water Quality Objectives (WQOs), Beneficial Uses and the States Policy on Maintaining High Quality Waters³. The WQOs serve as the primary basis for protecting the associated Beneficial Use. The Numeric Target of a TMDL interprets and applies the numeric and/or narrative WQOs of the WQSs as the basis for the WLAs. This Order addresses TMDLs through Water Quality Based Effluent Limitations (WQBELs) that must be consistent with the assumptions and requirements of the WLA⁴. Federal guidance⁵ states that when adequate information exists, storm water permits are to incorporate numeric water quality based effluent limitations. In most cases, the numeric target(s) of a TMDL are a component of the WQBELs. When the numeric target is based on one or more numeric WQOs, the numeric WQOs and underlying assumptions and requirements will be used in the WQBELs as numeric effluent limitations by the end of the TMDL compliance schedule, unless additional information is required. When the numeric target interprets one or more narrative WQOs, the numeric target may assess the efficacy and progress of the BMPs in meeting the WLAs and restoring the Beneficial Uses by the end of the TMDL compliance schedule.

This Order fulfills a component of the TMDL Implementation Plan adopted by this Regional Board on June 11, 2008 for indicator bacteria in Baby Beach by establishing WQBELs expressed as both BMPs to achieve the WLAs and as numeric limitations⁶ for the City of Dana Point and the County of Orange. The establishment of WQBELs expressed as BMPs should be sufficient to achieve the WLA specified in the TMDL. The Waste Load Allocations (WLAs) and Numeric Targets are the necessary metrics to ensure that the BMPs achieve appropriate concentrations of bacterial indicators in the receiving waters.

³ State Water Resources Control Board, Resolution No. 68-16

⁴ 40 CFR 122.44(d)(1)(vii)(B)

⁵ USEPA, *Interim Permitting Approach for Water Quality-Based Effluent Limitations in Storm Water Permits*, 61 FR 43761, August 26, 1996

⁶ The Waste Load Allocations are defined in Resolution No. R9-2008-0027, A Resolution to Adopt an Amendment to the *Water Quality Control Plan for the San Diego Basin (9)* to Incorporate Total Maximum Daily Loads for Indicator Bacteria, Baby Beach in Dana Point Harbor and Shelter Island Shoreline Park in San Diego Bay.

12. This Order requires each Copermittee to effectively prohibit all types of unauthorized discharges of non-storm water into its MS4. However, historically pollutants have been identified as present in dry weather non-storm water discharges from the MS4s through 303(d) listings, monitoring conducted by the Copermittees under Order No. R9-2002-0001, and there are others expected to be present in dry weather non-storm water discharges because of the nature of these discharges. This Order includes action levels for pollutants in non-storm water, dry weather, discharges from the MS4 designed to ensure that the requirement to effectively prohibit all types of unauthorized discharges of non-storm water in the MS4 is being complied with. Action levels in the Order are based upon numeric or narrative water quality objectives and criteria as defined in the Basin Plan, the Water Quality Control Plan for Ocean Waters of California (Ocean Plan), and the State Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California (State Implementation Policy or SIP). An exceedance of an action level requires specified responsive action by the Copermittees. This Order describes what actions the Copermittees must take when an exceedance of an action level is observed. Exceedances of non-storm water action levels do not alone constitute a violation of this Order but could indicate non-compliance with the requirement to effectively prohibit all types of unauthorized non-storm water discharges into the MS4 or other prohibitions established in this Order. Failure to undertake required source investigation and elimination action following an exceedance of 2a non-storm water action level (NAL or action level) is a violation of this Order. The Regional Board recognizes that use of action levels will not necessarily result in detection of all unauthorized sources of non-storm water discharges because there may be some discharges in which pollutants do not exceed established action levels. However, establishing NALs at levels appropriate to protect water quality standards is expected to lead to the identification of significant sources of pollutants in dry weather non-storm water discharges.
13. In addition to federal regulations cited in the Fact Sheet / Technical Report for the Order NO. R9-2009-0002, monitoring and reporting required under Order No. R9-2009-0002 is required pursuant to authority under CWC section 13383.

F. PUBLIC PROCESS

1. The Regional Board has notified the Copermittees, all known interested parties, and the public of its intent to consider adoption of an Order prescribing waste discharge requirements that would serve to renew an NPDES permit for the existing discharge of runoff.
2. The Regional Board has held public hearings on April 11, 2007, February 13, 2008, July 1, 2009, and November 18, 2009 and heard and considered all comments pertaining to the terms and conditions of this Order.

IT IS HEREBY ORDERED that the Copermittees, in order to meet the provisions contained in Division 7 of the California Water Code (CWC) and regulations adopted thereunder, and the provisions of the Clean Water Act (CWA) and regulations adopted thereunder, must each comply with the following:

A. PROHIBITIONS AND RECEIVING WATER LIMITATIONS

1. Discharges into and from municipal separate storm sewer systems (MS4s) in a manner causing, or threatening to cause, a condition of pollution, contamination, or nuisance (as defined in CWC section 13050), in waters of the state are prohibited.
2. Storm water discharges from MS4s containing pollutants which have not been reduced to the maximum extent practicable (MEP) are prohibited.⁷
3. Discharges from MS4s that cause or contribute to the violation of water quality standards (designated beneficial uses, water quality objectives developed to protect beneficial uses, and the State policy with respect to maintaining high quality waters) are prohibited.
 - a. ~~Each Copermittee must comply with section A.3 and section A.4 as it applies to Prohibition 5 in Attachment A of this Order through timely implementation of control measures and other actions to reduce pollutants in storm water discharges in accordance with this Order, including any modifications. If exceedance(s) of water quality standards persist notwithstanding implementation of this Order, the Copermittee must assure compliance with section A.3 and section A.4 as it applies to Prohibition 5 in Attachment A of this Order by complying with the following procedure:~~
 - (1) Upon a determination by either the Copermittee or the Regional Board that storm water MS4 discharges are causing or contributing to an exceedance of an applicable water quality standard, the Copermittee must notify the Regional Board within 30 days and thereafter submit a report to the Regional Board that describes best management practices (BMPs) that are currently being implemented and additional BMPs that will be implemented to prevent or reduce any pollutants that are causing or contributing to the exceedance of water quality standards. The report may be incorporated in the Annual Report unless the Regional Board directs an earlier submittal. The report must include an implementation schedule. The Regional Board may require modifications to the report;

⁷ This prohibition does not apply to MS4 discharges which receive subsequent treatment to reduce pollutants to the MEP prior to entering receiving waters (e.g., low flow diversions to the sanitary sewer).

- (2) Submit any modifications to the report required by the Regional Board within 30 days of notification;
 - (3) Within 30 days following approval of the report described above by the Regional Board, the Copermittee must revise its Jurisdictional Runoff Management Program and monitoring program to incorporate the approved modified BMPs that have been and will be implemented, the implementation schedule, and any additional monitoring required; and
 - (4) Implement the revised Jurisdictional Runoff Management Program and monitoring program in accordance with the approved schedule.
- b. The Copermittee must repeat the procedure set forth above to comply with the receiving water limitations for continuing or recurring exceedances of the same water quality standard(s) unless directed to do otherwise by the Regional Board Executive Officer.
 - c. Nothing in section A.3 must prevent the Regional Board from enforcing any provision of this Order while the Copermittee prepares and implements the above report.
4. In addition to the above prohibitions, discharges from MS4s are subject to all Basin Plan prohibitions cited in Attachment A to this Order.

B. NON-STORM WATER DISCHARGES

1. Each Copermittee must effectively prohibit all types of non-storm water discharges into its MS4 unless such discharges are either authorized by a separate National Pollutant Discharge Elimination System (NPDES) permit; or not prohibited in accordance with sections B.2 and B.3 below.
2. The following categories of non-storm water discharges are not prohibited unless a Copermittee or the Regional Board identifies the discharge category as a source of pollutants to waters of the U.S. Where the Copermittee(s) have identified a category as a source of pollutants, the category shall be addressed as an illicit discharge and prohibited through ordinance, order or similar means. The Regional Board may identify categories of discharge that either requires prohibition or other controls. For such a discharge category, the Copermittee, under direction of the Regional Board, must either prohibit the discharge category or develop and implement appropriate control measures to prevent the discharge of pollutants to the MS4 and report to the Regional Board pursuant to Section K.1 and K.3 of this Order.
 - a. Diverted stream flows;
 - b. Rising ground waters;
 - c. Uncontaminated ground water infiltration [as defined at 40 CFR 35.2005(20)] to

- MS4s;
- d. Uncontaminated pumped ground water⁸;
 - e. Foundation drains⁸;
 - f. Springs;
 - g. Water from crawl space pumps⁸;
 - h. Footing drains⁸;
 - i. Air conditioning condensation;
 - j. Flows from riparian habitats and wetlands;
 - k. Water line flushing^{9,10};
 - l. Discharges from potable water sources not subject to NPDES Permit No. CAG679001, other than water main breaks;
 - m. Individual residential car washing; and
 - n. Dechlorinated swimming pool discharges¹¹.
3. Emergency fire fighting flows (i.e., flows necessary for the protection of life or property) do not require BMPs and need not be prohibited. As part of the Jurisdictional Runoff Management Plan (JRMP), each Copermittee must develop and implement a program to address pollutants from non-emergency fire fighting flows (i.e., flows from controlled or practice blazes and maintenance activities) identified by the Copermittee to be significant sources of pollutants to waters of the United States.
- a. Building fire suppression system maintenance discharges (e.g. sprinkler line flushing) contain waste. Therefore, such discharges are to be prohibited by the Copermittees as illicit discharges through ordinance, order, or similar means.
4. Each Copermittee must examine all dry weather effluent analytical monitoring results collected in accordance with section F.4 of this Order and Receiving Waters and MS4 Discharge Monitoring and Reporting Program No. R9-2009-0002 to identify water quality problems which may be the result of any non-prohibited discharge category(ies) identified above in section B.2. Follow-up investigations must be conducted as necessary to identify and control, pursuant to section B.2, any non-prohibited discharge category(ies) listed above.

⁸ Requires enrollment under Order R9-2008-002. Discharges into the MS4 require authorization from the owner and operator of the MS4 system.

⁹ This exemption does not include fire suppression sprinkler system maintenance and testing discharges. Those discharges may be regulated under Section B.3.

¹⁰ Requires enrollment under Order R9-2002-0020.

¹¹ Including saline swimming pool discharges directly to a saline water body.

C. NON-STORM WATER DRY WEATHER ACTION LEVELS

1. Each Copermitttee, beginning no later than May 1, 2011, shall implement the non-storm water dry weather action level (NAL) monitoring as described in Attachment E of this Order.
2. In response to an exceedance of an NAL, each Copermitttee must investigate and identify the source of the exceedance in a timely manner. However, if any Copermitttee identifies exceedances of NALs that prevent them from adequately conducting source investigations in a timely manner, then the Copermitttees may submit a prioritization plan and timeline that identifies the timeframe and planned actions to investigate and report their findings on all of the exceedances. Following the source investigation and identification, the Copermitttees must submit an action report dependant on the source of the pollutant exceedance as follows:
 - a. If the Copermitttee identifies the source of the exceedance as natural (non-anthropogenically influenced) in origin and in conveyance into the MS4; then the Copermitttee shall report their findings and documentation of their source investigation to the Regional Board within fourteen days of the source identification.
 - b. If the Copermitttee identifies the source of the exceedance as an illicit discharge or connection, then the Copermitttees must eliminate the discharge to their MS4 and report the findings, including any enforcement action(s) taken, and documentation of the source investigation to the Regional Board within fourteen days of the source identification. If the Copermitttee is unable to eliminate the source of discharge within fourteen days, then the Copermitttee must submit, as part of their action report, their plan and timeframe to eliminate the source of the exceedance. Those dischargers seeking to continue such a discharge must become subject to a separate NPDES permit prior to continuing any such discharge.
 - c. If the Copermitttee identifies the source of the exceedance as an exempted category of non-storm water discharge, then the Copermitttees must determine if this is an isolated circumstance or if the category of discharges must be addressed through the prevention or prohibition of that category of discharge as an illicit discharge. The Copermitttee must submit their findings in including a description of the steps taken to address the discharge and the category of discharge, to the Regional Board for review with the next subsequent annual report. Such description shall include relevant updates to or new ordinances, orders, or other legal means of addressing the category of discharge. The Copermitttees must also submit a summary of their findings with the Report of Waste Discharge.
 - d. If the Copermitttee identifies the source of the exceedance as a non-storm water discharge in violation or potential violation of an existing separate NPDES permit

- (e.g. the groundwater dewatering permit), then the Copermittee must report, within three business days, the findings to the Regional Board including all pertinent information regarding the discharger and discharge characteristics.
- e. If the Copermittee is unable to identify the source of the exceedance after taking and documenting reasonable steps to do so, then the Copermittee must identify the pollutant as a high priority pollutant of concern in the tributary subwatershed, perform additional focused sampling and update their programs within a year to reflect this priority. The Copermittee's annual report shall include these updates to their programs including, where applicable, updates to their watershed workplans (Section G.2), retrofitting consideration (Section F.3.d) and program effectiveness work plans (Section J.4).
 - f. The Copermittees or any interested party, may evaluate existing NALs and propose revised NALs for future Board consideration.
3. An exceedance of an NAL does not alone constitute a violation of the provisions of this Order, but an exceedance of an NAL may indicate lack of compliance with the requirement that Copermittees effectively prohibit all types of unauthorized non-storm water discharges into the MS4 or other prohibitions set forth in Sections A and B of this Order. Failure to timely implement required actions specified in this Order following an exceedance of an NAL constitutes a violation of this Order. However, neither compliance with NALs nor compliance with required actions following observed exceedances, excuses any non-compliance with the requirement to effectively prohibit all types of unauthorized non-storm water discharges into the MS4s or any non-compliance with the prohibitions in Sections A and B of this Order. NALs provide an assessment of the effectiveness of the prohibition of non-storm water discharges and of the appropriateness of exempted non-storm water discharges. During any annual reporting period in which one or more exceedances of NALs have been documented the Copermittee must submit with their next scheduled annual report, a report describing whether and how the observed exceedances did or did not result in a discharge from the MS4 that caused, or threatened to cause or contribute to a condition of pollution, contamination, or nuisance in the receiving waters.
4. Monitoring of effluent will occur at the end-of-pipe prior to discharge into the receiving waters, with a focus on Major Outfalls, as defined in 40 CFR 122.26(B 5-6) and Attachment E of this Order. The Copermittees must develop their monitoring plans to sample a representative percentage of major outfalls and identified stations within each hydrologic subarea. At a minimum, outfalls that exceed any NALs once during any year must be monitored in the subsequent year. Any station that does not exceed an NAL for 3 years may be replaced with a different station.

5. Each Copermittee shall monitor for the non-storm water dry weather action levels, which are incorporated into this Order as follows:

a. Action levels for discharges to inland surface waters:

Table 4.a.1: General Constituents

Parameter	Units	AMAL	MDAL	Instantaneous Maximum	Basis
Fecal Coliform	MPN/ 100 ml	200 ^A 400 ^B	-		BPO
Enterococci	MPN/ 100 ml	33	-	104 ^C	BPO/OP
Turbidity	NTU	-	20		BPO
pH	Units	Within limit of 6.5 to 8.5 at all times			BPO
Dissolved Oxygen	mg/L	Not less than 5.0 in WARM waters and not less than 6.0 in COLD waters			BPO
Total Nitrogen	mg/L	-	1.0	See MDEL	BPO
Total Phosphorus	mg/L	-	0.1	See MDEL	BPO
Methylene Blue Active Substances	mg/L	-	0.5	See MDEL	BPO

A – Based on a minimum of not less than five samples for any 30-day period

B – No more than 10 percent of total samples may exceed 400 per 100 ml during any 30 day period

C – This Value has been set to Ocean Plan Criteria for Designated Beach Areas

BPO – Basin Plan Objective

OP – Ocean Plan

MDAL – Maximum Daily Action Level

AMAL – Average Monthly Action Level

Table 4.a.2: Priority Pollutants

Parameter	Units	Freshwater (CTR)		Saltwater (CTR)	
		MDAL	AMAL	MDAL	AMAL
Cadmium	ug/L	*	*	16	8
Copper	ug/L	*	*	5.8	2.9
Chromium III	ug/L	*	*	-	-
Chromium VI (hexavalent)	ug/L	16	8.1	83	41
Lead	ug/L	*	*	14	2.9
Nickel	ug/L	*	*	14	6.8
Silver	ug/L	*	*	2.2	1.1
Zinc	ug/L	*	*	95	47

CTR – California Toxic Rule

* - Action Levels developed on a case-by-case basis (see below)

The NALs for Cadmium, Copper, Chromium (III), Lead, Nickel, Silver and Zinc will be developed on a case-by-case basis because the freshwater criteria are based on site-specific water quality data (receiving water hardness). For these priority pollutants, the following equations (40 CFR 131.38.b.2) will be required:

$$\begin{aligned} \text{Cadmium (Total Recoverable)} &= \exp(0.7852[\ln(\text{hardness})] - 2.715) \\ \text{Chromium III (Total Recoverable)} &= \exp(0.8190[\ln(\text{hardness})] + .6848) \\ \text{Copper (Total Recoverable)} &= \exp(0.8545[\ln(\text{hardness})] - 1.702) \\ \text{Lead (Total Recoverable)} &= \exp(1.273[\ln(\text{hardness})] - 4.705) \end{aligned}$$

$$\begin{aligned} \text{Nickel (Total Recoverable)} &= \exp(.8460[\ln(\text{hardness})] + 0.0584) \\ \text{Silver (Total Recoverable)} &= \exp(1.72[\ln(\text{hardness})] - 6.52) \\ \text{Zinc (Total Recoverable)} &= \exp(0.8473[\ln(\text{hardness})] + 0.884) \end{aligned}$$

b. Action levels for discharges to bays, harbors and lagoons/estuaries:

Table 4.b: General Constituents

Parameter	Units	AMAL	MDAL	Instantaneous Maximum	Basis
Total Coliform	MPN/100 ml	1,000	-	10,000	BPO
Fecal Coliform	MPN/100 ml	200 ^A , 400 ^B	-		BPO
Enterococci	MPN/100 ml	35	-	104 ^C	BPO
Turbidity	NTU	75	-	225	OP
pH	Units	Within limit of 6.0 to 9.0 at all times			OP
Priority Pollutants	ug/L	See limitations in Table 4.a.2			

A – Based on a minimum of not less than five samples for any 30-day period

B – No more than 10 percent of total samples may exceed 400 per 100 ml during any 30 day period

C – Designated Beach Areas

OP – California Ocean Plan 2005

BPO – Basin Plan Objective

MDAL – Maximum Daily Action Level

AMAL – Average Monthly Action Level

c. Action levels for discharges to the surf zone:

Table 4.c: General Constituents

Parameter	Units	AMAL	MDAL	Instantaneous Maximum	Basis
Total Coliform	MPN/100 ml	1,000	-	10,000 1,000 ^A	OP
Fecal Coliform	MPN/100 ml	200 ^B	-	400	OP
Enterococci	MPN/100 ml	35	-	104 ^C	OP

A – Total coliform density shall not exceed 1,000 per 100 ml when the ratio of fecal/total coliform exceeds 0.1

B – During any 30 day period

C – Designated Beach Areas

OP – California Ocean Plan 2005

D. STORM WATER ACTION LEVELS

1. Beginning Year 3 after Order adoption date, a running average of twenty percent or greater of exceedances of any discharge of storm water from the MS4 to waters of the United States that exceed the Storm Water Action Levels (SALs) for the pollutants listed in Table 5 (below) will require each Copermitttee to affirmatively augment and implement all necessary storm water controls and measures to reduce the discharge of the associated class of pollutants(s) to the MEP standard. The Copermitttees must utilize the exceedance information when adjusting and executing annual work plans, as required by this Order. Copermitttees shall take the magnitude, frequency, and number of constituents exceeding the SAL(s), in addition to receiving water quality data and other information, into consideration when reacting to SAL exceedances in an iterative manner. Failure to appropriately consider and react to SAL exceedances in an iterative manner creates a presumption that the Copermitttee(s) have not complied with the MEP standard.

Table 5. Storm Water Action Levels

Pollutant	Action Level
Turbidity (NTU)	126
Nitrate & Nitrite total (mg/L)	2.6
P total (mg/L)	1.46
Cd total (µg/L)	3.0
Cu total (µg/L)	127
Pb total (µg/L)	250
Ni total (µg/L)	54
Zn total (µg/L)	976

2. The end-of-pipe assessment points for the determination of SAL compliance are all major outfalls, as defined in 40 CFR 122.26(b)(5) and (b)(6). The Copermitttees must develop their monitoring plans to sample a representative percent of the major outfalls within each hydrologic subarea. At a minimum, outfalls that exceed SALs must be monitored in the subsequent year. Any station that does not exceed an SAL for 3 years may be replaced with a different station. SAL samples must be 24 hour time weighted composites.
3. The absence of SAL exceedances does not relieve the Copermitttees from implementing all other required elements of this Permit.
4. This Permit does not regulate natural sources and conveyances of constituents listed in Table 5. To be relieved of the requirements to prioritize pollutant/watershed combinations for BMP updates and to continue monitoring a station, the Copermitttee must demonstrate that the likely and expected cause of the SAL exceedance is not anthropogenic in nature.
5. The SALs will be reviewed and updated at the end of every permit cycle. The data collected pursuant to D.2 above can be used to create SALs based upon local data.

It is the goal of the SALs, through the iterative and MEP process, to have outfall storm water discharges meet all applicable water quality standards.

E. LEGAL AUTHORITY

1. Each Copermitttee must establish, maintain, and enforce adequate legal authority to control pollutant discharges into and from its MS4 through ordinance, statute, permit, contract or similar means. Nothing herein shall authorize a Co-Permitttee or other discharger regulated under the terms of this order to divert, store or otherwise impound water if such action is reasonably anticipated to harm downstream water right holders in the exercise of their water rights. This legal authority must, at a minimum, authorize the Copermitttee to:
 - a. Control the contribution of pollutants in discharges of runoff associated with industrial and construction activity to its MS4 and control the quality of runoff from industrial and construction sites. This requirement applies both to industrial and construction sites which have coverage under the statewide general industrial or construction storm water permits, as well as to those sites which do not. Grading ordinances must be updated and enforced as necessary to comply with this Order;
 - b. Prohibit all identified illicit discharges not otherwise allowed pursuant to section B.2;
 - c. Prohibit and eliminate illicit connections to the MS4;
 - d. Control the discharge of spills, dumping, or disposal of materials other than storm water to its MS4;
 - e. Require compliance with conditions in Copermitttee ordinances, permits, contracts or orders (i.e., hold dischargers to its MS4 accountable for their contributions of pollutants and flows);
 - f. Utilize enforcement mechanisms to require compliance with Copermitttee storm water ordinances, permits, contracts, or orders;
 - g. Control the contribution of pollutants from one portion of the shared MS4 to another portion of the MS4 through interagency agreements among Copermitttees. Control of the contribution of pollutants from one portion of the shared MS4 to another portion of the MS4 through interagency agreements with other owners of the MS4 such as the State of California Department of Transportation, the United States Department of Defense, or Native American Tribes is encouraged;
 - h. Carry out all inspections, surveillance, and monitoring necessary to determine compliance and noncompliance with local ordinances and permits and with this Order, including the prohibition on illicit discharges to the MS4. This means the Copermitttee must have authority to enter, monitor, inspect, take measurements, review and copy records, and require regular reports from industrial facilities discharging into its MS4, including construction sites;
 - i. Require the use of BMPs to prevent or reduce the discharge of pollutants into MS4s from storm water to the MEP; and

