

**CALIFORNIA WATER QUALITY CONTROL BOARD
SAN DIEGO REGION
MONITORING AND REPORTING PROGRAM NO. 96-13
FOR THE
COUNTY OF SAN DIEGO
PALOMAR AIRPORT SANITARY LANDFILL**

A. MONITORING PROVISIONS

1. All analyses shall be performed in a laboratory certified to perform such analyses by the California Department of Health Services or a laboratory approved by the Executive Officer. Specific methods of analysis must be identified. If methods other than U. S. EPA approved methods or Standard Methods are used, the exact methodology must be submitted for review and must be approved by the Executive Officer prior to use. The director of the laboratory whose name appears on the certification shall supervise all analytical work in his/her laboratory and shall sign all reports of such work submitted to the Regional Board.
2. If the discharger monitors any pollutants more frequently than required by this Order, using the most recent version of Standard U. S. EPA Methods, or as specified in this Order, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the discharger's monitoring report. The increased frequency of monitoring shall also be reported.
3. The discharger shall report all instances of noncompliance not reported under Reporting Requirement D.5 of this Order at the time monitoring reports are submitted. The reports shall contain the information listed in Reporting Requirement D.5.
4. Sample collection, storage, and analysis shall be performed according to the most recent version of Standard U. S. EPA Methods, and in accordance with an approved sampling and analysis plan.
5. All monitoring instruments and equipment which are used by the discharger to fulfill the prescribed monitoring program shall be properly calibrated and maintained as necessary to ensure their continued accuracy.
6. The discharger shall retain records of all monitoring information, including all calibration and maintenance records and copies of all reports required by this Order. Records shall be maintained for a minimum of five years from the date of the sample, measurement, report or application. This period may be extended during the course of any unresolved litigation regarding this discharge or when requested by the Executive Officer.

7. Records of monitoring information shall include:
 - a. The date, identity of sample, Monitoring Point from which it was taken, and time of sampling or measurement;
 - b. The individual(s) who performed the sampling or measurements;
 - c. Date and time that analyses were started and completed, and the name of the personnel performing each analysis;
 - d. The analytical techniques or method used, including method of preserving the sample and the identity and volumes of reagents used;
 - e. Calculation of results; and
 - f. Results of analyses, and the MDL for each parameter.
 - g. Laboratory quality assurance results (e.g. percent recovery, response factor)
8. The monitoring reports shall be signed by an authorized person as required by Reporting Requirement D.9.

B. SITE MAINTENANCE

1. The discharger shall perform quarterly inspections of the landfill site and report the results **semi-annually**. The report shall contain information on the sites condition and a discussion of any significant findings with regard to:
 - a) General site condition;
 - b) Surface cover and slope;
 - c) Drainage facilities;
 - d) Ground water and vadose zone monitoring networks;
 - e) Methane gas control system;
 - f) Observation of seepage from the site; and
 - g) Maintenance activities at the site.

C. GROUND WATER AND UNSATURATED ZONE GAS SAMPLING/ANALYSIS FOR DETECTION MONITORING

1. The discharger shall establish and maintain groundwater wells at the landfill site to be used as part of the water quality monitoring program.
2. Prior to pumping monitoring wells for sampling, the static water level shall be measured in each well.

3. Prior to sampling monitoring wells, the presence of a floating immiscible layer in all wells shall be determined at the beginning of each sampling event. This shall be done prior to any other activity which may disturb the surface of the water in a well, e.g. water level measurements. If an immiscible layer is found, the Regional Board shall be notified within 24 hours.
4. The discharger shall submit a compliance evaluation summary of the groundwater data obtained. The summary shall contain a table which includes the following information:
 - a. Monitoring parameters;
 - b. Detection limit of monitoring equipment;
 - c. Measured concentrations found in the current sampling event
5. Water samples from the compliance points shall be collected, analyzed, and reported as shown in C.7 below.
6. **Ground Water Flow Rate/Direction**

For each monitored ground water body, the discharger shall measure the water level in each well and determine ground water flow rate and direction at least semi-annually, including the times of expected highest and lowest elevations of the water level for the respective ground water body. Ground water elevations for all background and downgradient wells for a given ground water body shall be measured within a period of time short enough to avoid temporal variations in ground water flow which could preclude accurate determination of ground water flow rate and direction.

7. GROUND WATER MONITORING

The following shall constitute the ground water monitoring program for the Palomar Airport Sanitary Landfill:

Constituent	Units		Sampling Frequency	Reporting Frequency
pH			Semi-annually	Semi-annually
TDS	mg/l		Semi-annually	Semi-annually
Chloride	mg/l		Semi-annually	Semi-annually
Nitrogen	mg/l		Semi-annually	Semi-annually
Sulfate	mg/l		Semi-annually	Semi-annually
Volatile Organics	µg/l		Semi-annually	Semi-annually
Antimony	mg/l		Semi-annually	Semi-annually
Arsenic	mg/l		Semi-annually	Semi-annually
Barium	mg/l		Semi-annually	Semi-annually
Beryllium	mg/l		Semi-annually	Semi-annually
Cadmium	mg/l		Semi-annually	Semi-annually
Chromium	mg/l		Semi-annually	Semi-annually
Cobalt	mg/l		Semi-annually	Semi-annually
Copper	mg/l		Semi-annually	Semi-annually
Iron	mg/l		Semi-annually	Semi-annually
Lead	mg/l		Semi-annually	Semi-annually
Magnesium	mg/l		Semi-annually	Semi-annually
Manganese	mg/l		Semi-annually	Semi-annually
Mercury	mg/l		Semi-annually	Semi-annually
Molybdenum	mg/l		Semi-annually	Semi-annually
Nickel	mg/l		Semi-annually	Semi-annually
Selenium	mg/l		Semi-annually	Semi-annually
Silver	mg/l		Semi-annually	Semi-annually
Thallium	mg/l		Semi-annually	Semi-annually
Vanadium	mg/l		Semi-annually	Semi-annually
Zinc	mg/l		Semi-annually	Semi-annually

Note: mg/l = milligrams/liter and µg/l = micrograms/liter

E. REPORTS TO BE FILED WITH THE BOARD

All reports shall be submitted no later than one month following the end of their respective Reporting Period. The reports shall be comprised of at least the following in addition to the specific contents listed for each respective report type:

1. Transmittal Letter

A letter summarizing the essential points shall be submitted with each report. The transmittal letter shall include:

- a. A discussion of any requirement violations found since the last such report was submitted and shall describe actions taken or planned for correcting the violations. If the discharger has previously submitted a detailed time schedule for correcting said requirement violations, a reference to the correspondence transmitting such schedule will be satisfactory. If no violations have occurred since the last submittal, this shall be stated in the transmittal letter; and
- b. A statement certifying that, under penalty of perjury, that to the best of the signer's knowledge the report is true, complete, and correct. This statement shall be signed by an individual that meets the requirements contained in Reporting Requirement D.9.

2. Semi-Annual Report

The semi-annual report shall contain, but not be limited to the following:

- a. Site maintenance outlined in section B of this Monitoring and Reporting Program.
- b. Groundwater analysis and flow rate outlined in section D of this Monitoring and Reporting Program.
- c. A map (or copy of an aerial photograph) showing the locations of observation stations, Monitoring Points, and Background Monitoring Points.

3. Annual Summary Report

The discharger shall submit an annual report to the Regional Board covering the previous monitoring year. The annual Reporting Period ends March 31.

- a. For each monitoring point, submit in graphical format the laboratory analytical data for all samples taken within at least the previous four calendar years. Each graph shall plot the concentration of the constituent over time for a given monitoring point, at a scale appropriate to show trends or variations in water quality.

- b. A comprehensive discussion of the compliance record, result of any corrective actions taken or planned which may be needed to bring the discharger into full compliance with the waste discharge requirements.
- c. A written summary of the monitoring results and monitoring system(s), indicating any changes made or observed since the previous annual report.
- d. A map showing the direction of ground water flow at the landfill site.

H. REPORTING


Monitoring reports shall be submitted to the Executive Officer in accordance with the following schedule:

<u>Report Frequency</u>	<u>Report Period</u>	<u>Report Due</u>
Semiannually	April - September	30 Days after
	October - March	the reporting
Annually	April - March	period.

Monitoring reports shall be submitted to:

California Regional Water Quality Control Board
San Diego Region
9771 Clairemont Mesa Blvd., Suite A
San Diego, CA 92124-1331

Ordered by


John H. Robertus
Executive Officer